

CONTAMINATION CONTROL SOLUTIONS



PASSION TO PERFORM



A WORLDWIDE LEADER IN THE FIELD OF HYDRAULIC FILTRATION EQUIPMENT.

Our company started life in 1964, when Bruno Pasotto decided to attempt to cater for the requests of a market still to be fully explored, with the study, design, development, production and marketing of a vast range of filters for hydraulic equipment, capable of satisfying the needs of manufacturers in all sectors. The quality of our products, our extreme competitiveness compared with major international producers and our constant activities of research, design and development has made us a worldwide leader in the field of hydraulic circuit filtering. Present for over 50 years in the market, we have played a truly decisive role in defining our sector, and by now we are a group capable of controlling our entire chain of production, monitoring all manufacturing processes to guarantee superior quality standards and to provide concrete solutions for the rapidly evolving needs of customers and the market.

1)



CONTAMINATION CONTROL SOLUTIONS



MP ...because contamination costs!





INDEX

(1	page	INTRODUCTION
	4	OMPANY PROFILE
	8	RODUCT RANGE
1	1	ONTAMINATION MANAGEMENT

18 page		CONTAMINATION MONITORING PRODUCTS
21	LPA3	Portable Laser Particle Analyzer
27	LPA2 Aviation Edition	Twin Laser Particle Analyser
33	CML4	Compact Portable Contamination Monitor
39	ICM 4.0	In-line Contamination Monitor - WiFi technology integrated
45	ICM 2.0	In-line Contamination Monitor
51	AZ2	ATEX Fluid Contamination Monitors
57	ICU	In-line Contamination Monitoring Unit
63	ACMU	Auxiliary Contamination Monitoring Unit
69	BS110 & BS500	Bottle Samplers
78	HOW SAMPLING	
81	PIK - Patch Imaging Kit	Patch Sampling and Digital Imaging Kit
84	FLUID COMPATIBILITY CHARTS	
88	SPARE PARTS LIST	
93	ACCESSORIES	

100 page		MOBILE FILTRATION UNITS
103	UFM 015	Mobile filtration unit 15 I/min flow rate
113	UFM 041	Mobile filtration unit 34 I/min flow rate
119	UFM 051	Mobile filtration unit 50 I/min flow rate
125	UFM 091	Mobile filtration unit 90 I/min flow rate
131	UFM 181	Mobile filtration unit 180 I/min flow rate
137	UFM 919	Mobile filtration unit 90 I/min and 180 I/min flow rate
143	FTU 080	Fluid transfer unit 15 I/min flow rate



MARKET **LEADER**



Our work is based on a skillful interaction between advanced technology and fine workmanship, **customizing products according to specific market requests**, focusing strongly on innovation and quality, and following every step in the manufacturing of both standard and special products, fully respecting customer expectations.

Our customer-oriented philosophy, which enables us to satisfy all customer requests **rapidly** and **with personalized products**, makes us a **dynamic and flexible enterprise**. The possibility of constantly controlling and monitoring the entire production process is essential to allow us to guarantee the quality of our products.

WORLDWIDE PRESENCE

Our foreign Branches enable us to offer a diversified range of products that allow us to successfully face the aggressive challenge of international competition, and also to maintain a stable presence at a local level.

The Group boasts **10** business branches



TECHNOLOGY

Our constant **quest for excellence in quality and technological innovation** allows us to offer only the best solutions and services for applications in many fields, including general industry, test rigs, lubrication, heavy engineering, renewable energies, naval engineering, offshore engineering, aviation systems, emerging technologies and mobile plant (i.e. tractors, excavators, concrete pumps, platforms).







AND PRODUCTION

Our high level of technological expertise means we can rely entirely on our own resources, without resorting to external providers. This in turn enables us to satisfy a growing number of customer requests, also exploiting our constantly updated range of machines and equipment, featuring fully-automated workstations capable of 24-hour production.











Flow rates up to 875 l/min

Mounting:

- Tank immersed
- In-Line
- In tank with
- shut off valve
- In tank
- with flooded suction





RETURN / SUCTION FILTERS

Flow rates up to 300 l/min

Pressure up to 80 bar

Mounting: - In-Line - Tank top

SPIN-ON **FILTERS**

Flow rates up to 365 l/min

> Pressure up to 35 bar

Mounting: - In-Line

LOW & MEDIUM PRESSURE **FILTERS**

Flow rates up to 3000 l/min

Pressure up to 80 bar

- Parallel manifold version



PRESSURE FILTERS

Flow rates up to 750 l/min

Pressure from 110 bar up to 560 bar

- Mounting:
- In-Line
- Manifold
- In single
 - and duplex designs

up to 3000 l/min Pressure up to 20 bar

RETURN

FILTERS

Flow rates

Mounting: - In-Line - Tank top - In single

8

and duplex designs

- Tank top

Mounting: - In-Line - In single





PRODUCT RANGE

MP Filtri can offer a vast and articulated range of products for the global market, suitable for all industrial sectors using hydraulic equipment.

This includes filters (suction, return, return/suction, spin-on, pressure, stainless steel pressure, ATEX filters) and structural components (motor/pump bell-housings, transmission couplings, damping rings, foot brackets, aluminium tanks, cleaning covers).

We can provide all the skills and solutions required by the modern hydraulics industry to monitor contamination levels and other fluid conditions.

Mobile filtration units and a full range of accessories allow us to supply everything necessary for a complete service in the hydraulic circuits.



STAINLESS STEEL HIGH PRESSURE FILTERS

Flow rates up to 150 l/min

Pressure from 320 bar up to 1000 bar

Mounting:

- In-Line
- Manifold
- In single

and duplex designs



FILTERS FOR POTENTIALLY EXPLOSIVE ATMOSPHERE

Flow rates up to 154 l/min

Pressure from 420 bar up to 1000 bar

Mounting: - In-Line



CONTAMINATION CONTROL SOLUTIONS

Off-line, in-line particle counters Off-line bottle sampling products

- Fully calibrated using relevant ISO standards
- A wide range of variants to support fluid types and communication protocols
 Mobile Filtration Units with flow rates from 15 l/min up to 200 l/min



POWER TRANSMISSION PRODUCTS

 Aluminium bell-housings for motors

- from 0.12 kW to 400 kW
- Couplings in Aluminium
- Cast Iron Steel
- Damping rings
- Foot bracket
- Aluminium tanks
- Cleaning covers

TANK ACCESSORIES

- Oil filler and

- air breather plugs
- Optical and electrical level gauges
- Pressure gauge valve
- selectors
- Pipe fixing brackets
- Pressure gauges

q

Introduction



Contamination management

INDEX

		Page
(1)	HYDRAULIC FLUIDS	12
2	FLUIDS CONTAMINATION	12
3	EFFECTS OF CONTAMINATION ON HYDRAULIC COMPONENTS	12
4	MEASURING THE SOLID CONTAMINATION LEVEL	13
5	RECOMMENDED CONTAMINATION CLASSES	16
6	WATER IN HYDRAULIC AND LUBRICATING FLUIDS	17



1 HYDRAULIC FLUIDS

The fluid is the vector that transmits power, energy within an oleodynamic circuit. In addition to transmitting energy through the circuit, it also performs additional functions such as lubrication, protection and cooling of the surfaces. The classification of fluids used in hydraulic systems is coded in many regulatory references, different Standards.

The most popular classification criterion divides them into the following families: - MINERAL OILS

Commonly used oil deriving fluids.

- FIRE RESISTANT FLUIDS Fluids with intrinsic characteristics of incombustibility or high flash point.
- SYNTHETIC FLUIDS Modified chemical products to obtain specific optimized features.
- ECOLOGICAL FLUIDS

Synthetic or vegetable origin fluids with high biodegradability characteristics.

The choice of fluid for an hydraulic system must take into account several parameters.

These parameters can adversely affect the performance of an hydraulic system, causing delay in the controls, pump cavitation, excessive absorption, excessive temperature rise, efficiency reduction, increased drainage, wear, jam/block or air intake in the plant.

The main properties that characterize hydraulic fluids and affect their choice are:

- DYNAMIC VISCOSITY
- It identifies the fluid's resistance to sliding due to the impact of the particles forming it.
- KINEMATIC VISCOSITY

It is a widespread formal dimension in the hydraulic field.

It is calculated with the ratio between the dynamic viscosity and the fluid density.

Kinematic viscosity varies with temperature and pressure variations.

- VISCOSITY INDEX

This value expresses the ability of a fluid to maintain viscosity when the temperature changes.

A high viscosity index indicates the fluid's ability to limit viscosity variations by varying the temperature.

- FILTERABILITY INDEX

It is the value that indicates the ability of a fluid to cross the filter materials. A low filterability index could cause premature clogging of the filter material.

- WORKING TEMPERATURE

Working temperature affects the fundamental characteristics of the fluid. As already seen, some fluid characteristics, such as cinematic viscosity, vary with the temperature variation.

When choosing a hydraulic oil, must therefore be taken into account of the environmental conditions in which the machine will operate.

- COMPRESSIBILITY MODULE

Every fluid subjected to a pressure contracts, increasing its density. The compressibility module identifies the increase in pressure required to cause a corresponding increase in density.

- HYDROLYTIC STABILITY

It is the characteristic that prevents galvanic pairs that can cause wear in the plant/system.

12

- ANTIOXIDANT STABILITY AND WEAR PROTECTION These features translate into the capacity of a hydraulic oil to avoid corrosion of metal elements inside the system.
- HEAT TRANSFER CAPACITY
 It is the characteristic that indicates the capacity of hydraulic oil to exchange heat with the surfaces and then cool them.

2 FLUID CONTAMINATION

Whatever the nature and properties of fluids, they are inevitably subject to contamination. Fluid contamination can have two origins:

- INITIAL CONTAMINATION

Caused by the introduction of contaminated fluid into the circuit, or by incorrect storage, transport or transfer operations.

- PROGRESSIVE CONTAMINATION

Caused by factors related to the operation of the system, such as metal surface wear, sealing wear, oxidation or degradation of the fluid, the introduction of contaminants during maintenance, corrosion due to chemical or electrochemical action between fluid and components, cavitation. The contamination of hydraulic systems can be of different nature:

- SOLID CONTAMINATION

For example rust, slag, metal particles, fibers, rubber particles, paint particles - or additives

- LIQUID CONTAMINATION

For example, the presence of water due to condensation or external infiltration or acids

- GASEOUS CONTAMINATION

For example, the presence of air due to inadequate oil level in the tank, drainage in suction ducts, incorrect sizing of tubes or tanks.

3 EFFECTS OF CONTAMINATION ON HYDRAULIC COMPONENTS

Solid contamination is recognized as the main cause of malfunction, failure and early degradation in hydraulic systems. It is impossible to delete it completely, but it can be effectively controlled by appropriate devices.



Solid contamination mainly causes surface damage and component wear.

- SURFACE EROSION

Cause of leakage through mechanical seals, reduction of system performance, variation in adjustment of control components, failures.

- ADHESION OF MOVING PARTS Cause of failure due to lack of lubrication.
- DAMAGES DUE TO FATIGUE Cause of breakdowns and components breakdown.



ADHESION





Liquid contamination mainly results in decay of lubrication performance and protection of fluid surfaces.

DISSOLVED WATER

- INCREASING FLUID ACIDITY Cause of surface corrosion and premature fluid oxidation
- GALVANIC COUPLE AT HIGH TEMPERATURES Cause of corrosion

FREE WATER - ADDITIONAL EFFECTS

- DECAY OF LUBRICANT PERFORMANCE Cause of rust and sludge formation, metal corrosion and increased solid contamination
- BATTERY COLONY CREATION Cause of worsening in the filterability feature
- ICE CREATION AT LOW TEMPERATURES Cause damage to the surface
- ADDITIVE DEPLETION Free water retains polar additives

Gaseous contamination mainly results in decay of system performance.

- CUSHION SUSPENSION Cause of increased noise and cavitation.
- FLUID OXIDATION Cause of corrosion acceleration of metal parts.

- MODIFICATION OF FLUID PROPERTIES (COMPRESSIBILITY MODULE, DENSITY, VISCOSITY)
 Cause of system's reduction of efficiency and of control.
 It is easy to understand how a system without proper contamination management is subject to higher costs than a system that is provided.
- MAINTENANCE Maintenance activities, spare parts, machine stop costs
- ENERGY AND EFFICIENCY Efficiency and performance reduction due to friction, drainage, cavitation.

4 MEASURING THE SOLID CONTAMINATION LEVEL

The level of contamination of a system identifies the amount of contaminant contained in a fluid.

This parameter refers to a unit volume of fluid.

The level of contamination may be different at different points in the system. From the information in the previous paragraphs it is also apparent that the level of contamination is heavily influenced by the working conditions of the system, by its working years and by the environmental conditions.

What is the size of the contaminating particles that we must handle in our hydraulic circuit?







HUMAN HAIR (75 μm)

MINIMUM DIMENSION VISIBLE WITH HUMAN EYES (40 µm) TYPICAL CONTAMINANT DIMENSION IN A HYDRAULIC CIRCUIT (4-14 µm)

Contamination level analysis is significant only if performed with a uniform and repeatable method, conducted with standard test methods and suitably calibrated equipment.

To this end, ISO has issued a set of standards that allow tests to be conducted and express the measured values in the following ways.

- GRAVIMETRIC LEVEL - ISO 4405

The level of contamination is defined by checking the weight of particles collected by a laboratory membrane. The membrane must be cleaned, dried and desiccated, with fluid and conditions defined by the Standard.

The volume of fluid is filtered through the membrane by using a suitable suction system. The weight of the contaminant is determined by checking the weight of the membrane before and after the fluid filtration.



MEMBRANE



Contaminated Membrane

- CUMULATIVE DISTRIBUTION OF THE PARTICLES SIZE - ISO 4406

The level of contamination is defined by counting the number of particles of certain dimensions per unit of volume of fluid. Measurement is performed by Automatic Particle Counters (APC).

Following the count, the contamination classes are determined, corresponding to the number of particles detected in the unit of fluid.

The most common classification methods follow ISO 4406 and SAE AS 4059 (Aerospace Sector) regulations.

NAS 1638 is still used although obsolete.

Classification example according to ISO 4406

The International Standards Organisation standard ISO 4406 is the preferred method of quoting the number of solid contaminant particles in a sample.

The code is constructed from the combination of three scale numbers selected from the following table.

The first number represents the number of particles that are larger than 4 $\mu m_{\text{(c)}}$

The second number represents the number of particles larger than 6 μ m_(c). The third scale number represents the number of particles in a millilitre sample of the fluid that are larger than 14 μ m_(c).

ISO 4406 - Allocation of Scale Numbers

Class	Number of particles per ml		
	Over	Up to	
28	1 300 000	2 500 000	
27	640 000	1 300 000	
26	320 000	640 000	
25	160 000	320 000	
24	80 000	160 000	
23	40 000	80 000	
22	20 000	40 000	
21	10 000	20 000	
20	5 000	10 000	
19	2 500	5 000	
18	1 300	2 500	
17	640	1 300	
16	320	640	
15	160	320	
14	80	160	
13	40	80	
12	20	40	
11	10	20	
10	5	10	
9	2.5	5	
8	1.3	2.5	
7	0.64	1.3	
6	0.32	0.64	
5	0.16	0.32	
4	0.08	0.16	
3	0.04	0.08	
2	0.02	0.04	
1	0.01	0.02	
0	0	0.01	

> $4 \mu m_{(c)} = 350$ particles
> $6 \mu m_{(c)} = 100 \text{ particles}$
$> 14 \mu m_{(c)} = 25 \text{particles}$
16/14/12

14

ISO 4406 Cleanliness Code System

Microscope counting examines the particles differently to APCs and the code is given with two scale numbers only.

These are at 5 μ m and 15 μ m equivalent to the 6 μ m_(c) and 14 μ m_(c) of APCs.



- CUMULATIVE DISTRIBUTION OF THE PARTICLES SIZE - SAE AS 4059-1 and SAE AS 4059-2

Classification example according to

SAE AS4059 - Rev. E and SAE AS4059-2 - Rev. F

The code, prepared for the aerospace industry, is based on the size, quantity, and particle spacing in a 100 ml fluid sample. The contamination classes are defined by numeric codes, the size of the contaminant is identified by letters (A-F).

SAE AS4059 - REV. E

It can be made a differential measurement (Table 1) or a cumulative measurement (Table 2)

Table 1 - Class for differential measurement

Class	Dimension of contaminant Maximum Contamination Limits per 100 ml				
	6-14 μm _(c)	14-21 µm _(c)	21-38 µm _(c)	38-70 µm _(c)	>70 µm _(c)
00	125	22	4	1	0
0	250	44	8	2	0
1	500	89	16	3	1
2	1 000	178	32	6	1
3	2 000	356	63	11	2
4	4 000	712	126	22	4
5	8 000	1 425	253	45	8
6	16 000	2 850	506	90	16
7	32 000	5 700	1 012	180	32
8	64 000	11 400	2 025	360	64
9	128 000	22 800	4 050	720	128
10	256 000	45 600	8 100	1 440	256
11	512 000	91 200	16 200	2 880	512
12	1 024 000	182 400	32 400	5 760	1 024

6 - 14 μm _(c) = 1	5 000 particles
14 - 21 μm _(c) =	2 200 particles
21 - 38 µm _(c) =	200 particles
38 - 70 μm _(c) =	35 particles
> 70 µm _(c) =	3 particles
SAE AS4059 REV	E - Class 6

Table 2 - Class for cumulative measurement

Class	Dimension of contaminant Maximum Contamination Limits per 100 ml					
	>4 µm _(c)	>6 µm _(c)	$>14 \ \mu m_{(c)}$	$>21 \ \mu m_{(c)}$	$>38 \ \mu m_{(c)}$	$>70 \ \mu m_{(c)}$
000	195	76	14	3	1	0
00	390	152	27	5	1	0
0	780	304	54	10	2	0
1	1 560	609	109	20	4	1
2	3 120	1 217	217	39	7	1
3	6 250	2 432	432	76	13	2
4	12 500	4 864	864	152	26	4
5	25 000	9 731	1 731	306	53	8
6	50 000	19 462	3 462	612	106	16
7	100 000	38 924	6 924	1 224	212	32
8	200 000	77 849	13 849	2 449	424	64
9	400 000	155 698	27 698	4 898	848	128
10	800 000	311 396	55 396	9 796	1 696	256
11	1 600 000	622 792	110 792	19 592	3 392	512
12	3 200 000	1 245 584	221 584	39 184	6 784	1 024

> $4 \mu m_{(c)} = 45000$ particles			
$> 6 \mu m_{(c)} = 15 000 \text{ particles}$			
$> 14 \ \mu m_{(c)} = 1500 \ particles$			
$> 21 \ \mu m_{(c)} = 250 \ particles$			
$> 38 \ \mu m_{(c)} = 15 \ particles$			
$> 70 \ \mu m_{(c)} = 3 \ particle$			
SAE AS4059 REV E 6A/6B/5C/5D/4E/2F			

The information reproduced on this page is a brief extract from SAE AS4059 Rev.E, revised in May 2005. For further details and explanations refer to the full Standard.

SAE AS4059 - REV. F

It can be made a differential measurement (Table 1) or a cumulative measurement (Table 2)

Table 1 - Class for differential measurement

Class	Dimension of contaminant Maximum Contamination Limits per 100 ml					(3)
	5-15 µm	15-25 µm	25-50 µm	50-100 µm	>100 µm	(1)
	6-14 μm _(c)	14-21 µm _(c)	21-38 µm _(c)	38-70 μm _(c)	>70 µm _(c)	(2)
00	125	22	4	1	0	
0	250	44	8	2	0	
1	500	89	16	3	1	
2	1 000	178	32	6	1	
3	2 000	356	63	11	2	
4	4 000	712	126	22	4	
5	8 000	1 425	253	45	8	•
6	16 000	2 850	506	90	16	
7	32 000	5 700	1 012	180	32	
8	64 000	11 400	2 025	360	64	
9	128 000	22 800	4 050	720	128	
10	256 000	45 600	8 100	1 440	256	
11	512 000	91 200	16 200	2 880	512	
12	1 024 000	182 400	32 400	5 760	1 024	_

6 - 14 µm _(c) =	15 000 particles
14 - 21 µm _(c) =	2 200 particles
21 - 38 µm _(c) =	200 particles
38 - 70 µm _(c) =	35 particles
> 70 µm _(c) =	3 particles
SAE AS4059 RE	V F - Class 6

Size range, microscope particle counts, based on longest dimension as measured per AS598 or ISO 4407.
 Size range, APC calibrated per ISO 11171 or an optical or electron microscope with image analysis software, based on projected area equivalent diameter.
 Contamination classes and particle count limits are identical to NAS 1638.

	Table 2 - Class for cumulative measurement												
Class	Dimension of contaminant Maximum Contamination Limits per 100 ml												
	>1 µm	>5 µm	>5 μm >15 μm >25 μm >50 μm >100 μ										
	>4 µm _(c)	>6 µm _(c)	$>14 \ \mu m_{(c)}$	>21 µm _(c) >38 µm _(c) >70 µm _(c)		$>70 \ \mu m_{(c)}$ (2)						
000	195	76	14	3	1	0	_						
00	390	390 152 27 5 1											
0	780	780 304 54		10	2	0							
1	1 560	609	109	20	4	1							
2	3 120	1 217	217	39	7	1							
3	6 250	2 432	432	76	13	2							
4	12 500	4 864	864	152	26	4							
5	25 000	9 731	1 731	306	53	8							
6	50 000	19 462	3 462	612	106	16							
7	100 000	38 924	6 924	1 224	212	32							
8	200 000	77 849	13 849	2 449	424	64							
9	400 000	155 698	27 698	4 898	848	128							
10	800 000	311 396	55 396	9 796	1 696	256							
11	1 600 000	622 792	110 792	19 592	3 392	512							
12	3 200 000	1 245 584	221 584	39 184	6 784	1 024							

> $4 \,\mu m_{(c)} = 45\,000$ particles

• (-)		
$> 6 \mu m_{(c)} = 15$	5 000 particles	
$> 14 \ \mu m_{(c)} = $	1 500 particles	
> 21 µm _(c) =	250 particles	
> 38 µm _(c) =	15 particles	
> 70 µm _(c) =	3 particle	
SAE AS4059 RE	EV F 6/5/5/4/2	

* cumulative particle count

(1) Size range, optical microscope, based on longest dimension as measured per AS598 or ISO 4407.

(2) Size range, APC calibrated per ISO 11171 or an optical or electron microscope with image analysis software, based on projected area equivalent diameter.

- CLASSES OF CONTAMINATION ACCORDING TO NAS 1638 (January 1964)

The NAS system was originally developed in 1964 to define contamination classes for the contamination contained within aircraft components.

The application of this standard was extended to industrial hydraulic systems simply because nothing else existed at the time.

The coding system defines the maximum numbers permitted of 100 ml volume at various size intervals (differential counts) rather than using cumulative counts as in ISO 4406. Although there is no guidance given in the standard on how to quote the levels, most industrial users quote a single code which is the highest recorded in all sizes and this convention is used on MP Filtri APC's.

The contamination classes are defined by a number (from 00 to 12) which indicates the maximum number of particles per 100 ml, counted on a differential basis, in a given size bracket.

Size Range Classes (in microns)

				-	, ,								
	Maxin	num Contami	ination Limits	s per 100 ml									
Class	5-15	15-25	25-50	50-100	>100								
00	125	22	4	1	0								
0	250	44	8	2	0								
1	500	89	16	3	1								
2	1 000	178	32	6	1								
3	2 000	356	63	11	2								
4	4 000	712	126	22	4								
5	8 000	1 425	253	45	8								
6	16 000	2 850	506	90	16								
7	32 000	5 700	1 012	180	32								
8	64 000	11 400	2 025	360	64								
9	128 000	22 800	4 050	720	128								
10	256 000	45 600	8 100	1 440	256								
11	512 000	91 200	16 200	2 880	512								
12	1 024 000	182 400	32 400	5 760	1 024								

 $5 - 15 \,\mu m = 42\,000$ particles $15 - 25 \,\mu m = 2\,200 \,\mu m$ $25 - 50 \,\mu m = 150 \,particles$ 50 - 100 µm⊨ 18 particles > 100 µm 3 particles

Class NAS 8

- CUMULATIVE DISTRIBUTION OF THE PARTICLES SIZE - ISO 4407

The level of contamination is defined by counting the number of particles collected by a laboratory membrane per unit of fluid volume. The measurement is done by a microscope. The membrane must be cleaned, dried and desiccated, with fluid and conditions defined by the Standard. The fluid volume is filtered through the membrane, using a suitable suction system.

The level of contamination is identified by dividing the membrane into a predefined number of areas and by counting the contaminant particles using a suitable laboratory microscope.



Example figure 1 and 2	
ISO 4406	
SAE AS4059E Table 1	
NAS 1638	
SAE AS4059E Table 2	

COMPARISON PHOTOGRAPH'S 1 graduation = 10µm



Class 11

Class 12A/11B/11C

For other comparison photographs for contamination classes see the "Fluid Condition and Filtration Handbook".

16

Fia. 1

Class 5

Class 6A/5B/5C

- CLEANLINESS CODE COMPARISON

Although ISO 4406 standard is being used extensively within the hydraulics industry other standards are occasionally required and a comparison may be requested. The table below gives a very general comparison but often no direct comparison is possible due to the different classes and sizes involved.

ISO 4406	SAE AS4059 Table 2	SAE AS4059 Table 1	NAS 1638
> 4 µm _(c) 6 µm _(c) 14 µm _(c)	> 4 μm _(c) 6 μm _(c) 14 μm _(c)	4-6 6-14 14-21 21-38 38-70 >70	5-15 15-25 25-50 50-100 >100
23 / 21 / 18	13A / 12B / 12C	12	12
22 / 20 / 17	12A/11B/11C	11	11
21 / 19 / 16	11A / 10B / 10C	10	10
20 / 18 / 15	10A / 9B / 9B	9	9
19 / 17 / 14	9A / 8B / 8C	8	8
18 / 16 / 13	8A / 7B / 7C	7	7
17 / 15 / 12	7A / 6B / 6C	6	6
16 / 14 / 11	6A / 5B / 5C	5	5
15 / 13 / 10	5A / 4B / 4C	4	4
14 / 12 / 09	4A / 3B / 3C	3	3

(5) RECOMMENDED CONTAMINATION CLASSES

The table below, gives a selection of maximum contamination levels that are typically issued by component manufacturer.

These relate to the use of the correct viscosity mineral fluid. An even cleaner level may be needed if the operation

is severe, such as high frequency fluctuations in loading, high temperature or high failure risk.

Piston pumps						
with fixed flow rate	•					
Piston pumps			•			
with variable flow rate			•			
Vane pumps						
with fixed flow rate		•				
Vane pumps			-			
with variable flow			•			
Engines	•					
Hydraulic cylinders	•					
Actuators					•	
Test benches						•
Check valve	•					
Directional valves	•					
Flow regulating valves	•					
Proportional valves				•		
Servo-valves					•	
Flat bearings			•			
Ball bearings				•		
ISO 4406 CODE	20/18/15	19/17/14	18/16/13	17/15/12	16/14/11	15/13/10
Recommended	B _{20(c)}	B _{15(c)}	B _{10(c)}	B7(c)	B _{7(C)}	B _{5(c)}
filtration $\beta_{x(c)\geq 1.000}$	>1000	>1000	>1000	>1000	>1000	>1000

6 WATER IN HYDRAULIC AND LUBRICATING FLUIDS

Water Content

In mineral oils and non aqueous resistant fluids water is undesirable. Mineral oil usually has a water content of 50-300 ppm (@40°C) which it can support without adverse consequences.

Once the water content exceeds about 300 ppm the oil starts to appear hazy. Above this level there is a danger of free water accumulating in the system in areas of low flow. This can lead to corrosion and accelerated wear.

Similarly, fire resistant fluids have a natural water which may be different to mineral oil.



Saturation Levels

Since the effects of free (also emulsified) water is more harmful than those of dissolved water, water levels should remain well below the saturation point.

However, even water in solution can cause damage and therefore every reasonable effort should be made to keep saturation levels as low as possible. There is no such thing as too little water. As a guideline, we recommend maintaining saturation levels below 50% in all equipment.

TYPICAL WATER SATURATION LEVEL FOR NEW OILS Examples:

Hydraulic oil @ $30^{\circ}C = 200 \text{ ppm} = 100\%$ saturation Hydraulic oil @ $65^{\circ}C = 500 \text{ ppm} = 100\%$ saturation



W - Water and Temperature Sensing

"W" option, in MP Filtri Contamination Monitoring Products, indicates water content as a percentage of saturation and oil temperature in degrees centigrade. 100% RH corresponds to the point at which free water can exist in the fluid. i.e. the fluid is no longer able to hold the water in a dissolved solution.

The sensor can help provide early indication of costly failure due to free water, including but not exclusive to corrosion, metal surface fatigue e.g. bearing failure, reduced lubrication & load carrying characteristics.

Different oils have different saturation levels and therefore RH (relative humidity) % is the best and most practical measurement.

Water absorber

Water is present everywhere, during storage, handling and servicing.

MP Filtri filter elements feature an absorbent media which protects hydraulic systems from both particulate and water contamination.

MP Filtri's filter element technology is available with inorganic microfiber media with a filtration rating 25 µm (therefore identified with media designation WA025, providing absolute filtration of solid particles to $\beta_{\rm X(C)} = 1000$).

Absorbent media is made by water absorbent fibres which increase in size during the absorption process. Free water is thus bonded to the filter media and completely removed from the system (it cannot even be squeezed out).



Fabric that absorbs water

The Filter Media has absorbed water



By removing water from your fluid power system, you can prevent such key problems as:

- corrosion (metal etching)
- loss of lubricant power
- accelerated abrasive wear in hydraulic components
- valve-locking
- bearing fatigue
- viscosity variance (reduction in lubricating properties)
- additive precipitation and oil oxidation
- increase in acidity level
- increased electrical conductivity (loss of dielectric strength)
- slow/weak response of control systems

Product availability - UFM Series: UFM 041 - UFM 051 - UFM 091 - UFM 181 - UFM 919

You can see right through our results

It's no secret the presence of particles in the hydraulic fluid is the primary cause of failure, unreliability and short component life in hydraulic systems - whether they be fluid power, lubrication or fuel. We have developed an extensive range of products to help you safeguard your machines and systems from potential failure.

Benefits:

- Promptly measures and maintains the appropriate fluid cleanliness level
- Damages and downtime are minimised, reducing costs
- Provides a maintenance regime to immediately respond to an incident

Applications:

- Industrial hydraulic and lubrication systems
- Mobile hydraulics



Contamination Monitoring Products











Portable Laser Particle Analyzer





Description

Portable Laser Particle Analyzer

MP Filtri's new LPA3 is the most advanced portable particle counter in the world. Whether you are working in the lab or in the field, the LPA3 delivers a fast, accurate and comprehensive hydraulic health check in a robust yet portable package.

Its real-time monitoring and predictive maintenance technology safeguards machinery, enhances performance and productivity, and reduces costs and unplanned downtime. Featuring the latest breakthroughs in optical and photodiode technology, the new LPA3 enhances the reliability and longevity of complex hydraulic systems and is ideal for quality control in in-house manufacturing applications. The LPA3 is compatible with the full range of Bottle Samplers.



- Online/realtime monitoring
- Comprehensive hydraulic health check
- Proactive maintenance capabilities
- High-speed sample times
- Programmable 10.1" (25.6cm) touchscreen display
- Perfectly portable at just 10kg
- Programmable sample volumes
- Precision Instrument
- Live trend analysis option
- Measures and displays the following international standard formats; ISO 4406, NAS 1638, AS 4059E&F, GBT 14039, GJB420B
- Moisture and temperature sensing
- Data logging and enhanced 4000 test result memory
- Key performance information at a glance
- LPA View software (included)
- Ideal for hydraulic, lubrication, and subsea fluids
- Integrated printer
- Full accessories kit included



Scope of Supply

- 1 x LPA3 (*)
- 1 x M16x2 microbore pressure hose, 1500 mm long, pouch
- 1 x 2000 mm quick release waste hose for LPA3 and pouch
- 1 x 1L waste receptacle
- 1 x Power Lead c/w UK/EU/US/AUS/CN heads
- 1 x USB cable
- 1 x Digital USB copy of user guides/software/drivers
- 2 x Hard copy of calibration certificate
- 5 x Thermal printer paper
- 1 x Carry bag

(*) Specific model will be as per ordered item

See Accessories at page 93



Technical data

Technology High precision LED light extinction automatic optical particle counter

Particle Sizing >4, 6, 14, 21, 25, 38, 50, 70 μm_(c)

Analysis range ISO 4406 Codes 8 to 24 NAS 1638 Class 2 to 12 AS4059/ISO 11218 Rev E, Table 1 Size Codes 2-12 AS4059/ISO 11218 Rev E, Table 2 Size Codes, A: 000 TO 12, B: 00 to 12, C: 00 to 12, D: 2 to 12, E: 4-12, F: 7 to 12 AS4059 Rev F, Table 1 Size Codes 2-12 AS4059 Rev F, Table 2 Size Codes cpc [000 to 12, 00 to 12, 00 to 12, 2 to 12, 4 to 12, 7 to 12] GBT14039 Codes 8-24 GJB420B Size Codes, A: 000 to 12, B: 00 to 12, C: 00 to 12, D: 2 to 12, E: 4-12, F: 7 to 12 Please Note: Lower Limits are Test Volume dependent

 $\begin{array}{l} \textbf{Accuracy} \\ \pm \ 1/2 \ \text{ISO} \ \text{code for} \ 4, \ 6, \ 14 \ \mu\text{m}_{(c)} \\ \pm 1 \ \text{code for} \ 21, \ 25, \ 38, \ 50, \ 70 \ \mu\text{m}_{(c)} \end{array}$

Calibration Individually calibrated with ISO Medium Test Dust (MTD) based on ISO 11171, on equipment certified by I.F.T.S to ISO 11943

Viscosity range Up to 400 cSt

Fluid temperature Minimum: +5 °C Maximum: +80 °C

Ambient temperature Minimum: -10 °C Maximum: +80 °C

Pressure Minimum: 2.0 bar / 29 psi Maximum: 420 bar / 6092 psi static

Sample Volume Maximum 100 ml / 3.38 fl oz per pump stroke.

Test time Test volumes programmable by end user. Pre-set volumes also available.



How LPA3 works - www.mpfiltri.com/index.php/products/oil-service/lpa-3.html

Moisture Sensing % RH (Relative Humidity) ±3%

Temperature Measurement ±3 °C

Data Storage Approximately 4000 timestamped tests in the integral LPA3 memory

System Pressure Measurement ± 0.5% Full Scale Accuracy Min 10 bar

Communication options 2 USB output ports 1 x USB B type for direct connection to PC and software 1 x USB A type for direct data download to USB memory stick

Environmental Protection IP66 (Lid closed) IP54 (Lid open)

Weight / Dimensions 10 kg, Height 292 mm, Depth 155 mm, Width 435 mm

Supply Voltage 18 - 19VDC

Power Long-life Lithium Ion internal rechargeable battery (mains charger)

Software LPA View software (included)

LPA3 is supplied with a full software package and digital product information





FOCUS ON

Exclusive MP Filtri technology

Featuring the latest breakthroughs in LED and photodiode technology, the LPA3 delivers increased accuracy combined with excellent repeatability.

W-Option Water Saturation level (RH%) and fluid temperature sensor option.

P-Option Live Pressure Readout (bar/PSI) on display screen.

LED light source

A single point high accuracy LED measures particles across all sizes giving increased accuracy with excellent repeatability.





LPA View Software

The LPA View software is used with the LPA3, LPA2, CML2, CML4 and ICM particle counters. When connected to LPA View, MP Filtri CMPs can transfer results in realtime, or alternatively, historical results can be downloaded from the CMP's inbuilt memory.

- Runs on Windows XP, 7, and Windows 10
- Full adjustment & control of product settings, test times and alarms
- Easy test report generation
- Trend analysis
- Graphical display options
- Universal format across our contamination monitoring product range



Contamination Monitoring Products (24)



Dimensions



Designation & Ordering code

	AUTOMATIC	PARTICLE COUNTER LPA	3									
Series		Configuration example:	LPA3	W		Ρ	Ν	1	1	0	1	
LPA3	Portable Laser Particle Analyzer				_							
Moistu	re Sensor											
0	Without moisture and temperature sensor											
W	With moisture and temperature sensor											
Pressu	Without on corean inlet pressure diaplay											
0	Without on-screen inlet pressure display											
<u>r</u>	with on-screen milet pressure display											
Fluid c	ompatibility											
М	Mineral oil and synthetic fluid											
N	M type fluids & Subsea fluids and water based fluids (*)											
S	M & N type fluids & phosphate esters and aggressive fluids (*)											
Externa	al Result											
1	With on board printer											
Design	Reference											
0	Std option with full accessory kit and carry bag											
Countr												
1	IIK FU US AUS/CN			 						 		
-												

(*) $\,{\rm N}$ and ${\rm S}$ version, moisture sensor (W) not available

Available with Screen Protector (Part number 63.095000). Consult your local branch for further details







LPA2 Aviation Edition

Twin Laser Particle Analyser



AVIATION EDITION

Description

Contamination Monitoring Products

Twin Laser Particle Analyser - LPA20PSTA30

The Airbus-approved LPA2 Aviation Edition is a highly precise, lightweight & fully portable instrument that has been created exclusively for the Aviation industry. It can automatically measure and display particulate contamination, moisture and temperature levels in various hydraulic fluids. The LPA2 can be connected to the MP range of bottle sampler products to enable laboratory based particle counting. The LPA2 is a solution for online monitoring of contamination in your hydraulic fluid, providing an immediate hydraulic health check. It employs predictive maintenance procedures to help reduce downtime and in turn costs.

> Features & Benefits

- Airbus-approved

- LPA2 saves time: online/realtime monitoring
- Immediate hydraulic health check
- Predictive maintenance procedures can be employed
- Reduced downtime for MRO teams
- Reduced costs associated with downtime
- The lightest machine in its class
- Fully portable
- Precision Instrument
- Full Calibration based on ISO11171
- Measures and displays the following international standard formats; ISO 4406, NAS 1638, AS 4059E
- Moisture and temperature sensing
- Data logging and 600 test result memory
- Manual and remote control flexibility
- Full size QWERTY keyboard
- Various test programme settings
- Full accessories kit included
- Internal rechargeable battery capable of performing 100 tests between charges





- Scope of Supply
- 1 x LPA2 (Model: LPA20PSTA030)
- 1 x Airbus sampling valve adapter* and C spanner
- 1 x M16x2 microbore pressure hose, 2500mm long
- (For the Airbus Sampling Adaptor)
- 1 x EN6123-04 to M16x2 microbore pressure hose
- 2500mm long (compatible with A350 sampling valve)
- 1 x 1L waste receptacle
- 1 x 12V, 2A power adapter c/w UK/EU/US/AUS/CN heads
- 1 x 9 pin serial cable
- 1 x USB to serial converter
- 1 x 3 pin socket for external signals
- 1 x Hard copy of product user guide
- 1 x Digital copy of user guides/software/drivers
- 2 x Hard copy of calibration certificate 2 x Thermal printer paper
- 1 x Carry bag
- 1 x Airbus Operator's Guide
- T X AII DUS OPERALOR S GUIDE

(*) Specific model will be as per ordered item See Accessories page 93.



())) MPALTR

AVIATION EDITION

Technical data

Technology

Twin laser and twin optical diode detectors Based Light Extinction Automatic Optical Particle Analyser

Particle Sizing >4,6,14,21,25,38,50,70 μm_(c) to ISO 4406 Standard

Analysis range ISO 4406 Codes 8 to 24 NAS 1638 Class 2 to 12 AS4059/ISO 11218 Rev E, Table 1 Size Codes 2-12 AS4059/ISO 11218 Rev E, Table 2 Size Codes, A: 000 TO 12, B: 00 to 12, C: 00 to 12, D: 2 to 12, E: 4-12, F: 7 to 12 AS4059 Rev F, Table 1 Size Codes 2-12 AS4059 Rev F, Table 2 Size Codes cpc [000 to 12, 00 to 12, 00 to 12, 2 to 12, 4 to 12, 7 to 12] GBT14039 Codes 8-24 GJB420B Size Codes, A: 000 to 12, B: 00 to 12, C: 00 to 12, D: 2 to 12, E: 4-12, F: 7 to 12 Please Note: Lower Limits are Test Volume dependent

Accuracy Better than 3% typical

Calibration Each unit individually calibrated with ISO Medium Test Dust (MTD) based on ISO 11171, on equipment certified by I.F.T.S. to ISO 11943

Viscosity range Up to 400 cSt

Fluid temperature Minimum: +5 °C Maximum: +80 °C

Ambient Temperature Minimum: -10 °C Maximum: +80 °C

Pressure Max 400 bar / 5800 psi (gauge) Minimum 2.0 bar / 29 psi (gauge) required

Sample Volume / Test time 8 ml. (short): 2:50- Recommended for set up only 15 ml. (normal): 5:00 30 ml. (dynamic): 10:00 24 ml. (bottle sampler): 8:00 15 ml. (continuous): 5:00 Moisture Sensing % RH (Relative Humidity) ±3%

Temperature Measurement ±3%

Data Storage Up to 600 tests

Communication options RS232 9 pin D plug

System Pressure Measurement ± 0.5% Full Scale Accuracy Min 10 bar

Environmental Protection IP51 (lid open)

Weight / Dimensions LPA2: 9.8 kg, Height 218 mm, Depth 268 mm, Width 436 mm

LPA2 Aviation Edition with travel case - packed: 18.5 kg, Height 500 mm, Length 600 mm, Width 400 mm

Supply Voltage 9-36VDC

Power Internal rechargeable battery (mains charger)

Outer Casing Finish Anodised Aluminium

Wetted parts S - 316 stainless steel, perfluoro elastomer, sapphire, EPDM

Software LPA View software (included)

LPA2 is supplied with a full software package and digital product information





FOCUS ON

P-Option

Laser 1

Exclusive MP Filtri technology

Live Pressure Readout (bar) on display screen.

The combination of the two lasers with a unique optics and photodiode package enables the LPA2 to give increased accuracy combined with excellent repeatability.





Laser 2

Standard accuracy laser specifically designed for system contaminants between 6 $\mu m_{(c)}$ and 70 $\mu m_{(c)}.$

and 6 µm_(c) giving increased accuracy with excellent repeatability.

A single point high accuracy laser measures particles of contamination at $4 \,\mu m_{(c)}$

LPA View Software

The LPA View software is used with the LPA3, LPA2, CML2, CML4 and ICM particle counters. When connected to LPA View, MP Filtri CMPs can transfer results in realtime, or alternatively, historical results can be downloaded from the CMP's inbuilt memory.

- Runs on Windows XP, 7, and Windows 10
- Full adjustment & control of product settings, test times and alarms
- Easy test report generation
- Trend analysis
- Graphical display options
- Universal format across our contamination monitoring product range









Dimensions



Designation & Ordering code

	AUT	OMATIC PARTICL	E COUNTER LPA20P	STA30						
Serie <u>s</u>			Configuration example:	LPA2	0	Р	S	Т	A	30
LPA2	Twin Laser Particle Analyser	_								
		_								
Moistu	re Sensor									
0	Without moisture and temperature sensor	_								
Pressu	re Sensor									
P	With on-screen inlet pressure display	_								
		_								
Fluid c	ompatibility									
S	Phosphate ester and aggressive fluids	_								
Access	ories									
Т	Standard unit with travel case	_								
Bottle s	sampling options									
Α	With Airbus adaptor									
	·	_								
Design	reference									
30										

(()) MPALTRI









CML4

Compact Portable Contamination Monitor





Description

Contamination Monitoring Products

Compact Portable Contamination Monitor - CML4W0M001

A compact and portable contamination monitor that delivers a fast, accurate assessment of contamination in the field and is the perfect solution for the mobile, construction and plant hire sectors. Easy to master, the new CML4 features cutting-edge contamination control technology to anyone wishing to protect their critical systems.

The CML4 features a metering pump which enables analysis of both 'live' and unpressurised systems, delivering comprehensive contamination checks on any machine in any condition.

> Features & Benefits

- High-resolution 7" (178 mm) touchscreen display
- Real-time contamination results at-a-glance
- High-speed sample times
- Predictive maintenance enabled
- Unpressurised and pressurised sampling up to 350 bar
- Fully portable at just 8.5 kg
- Precision Instrument
- Easy to master operators can get up and running in minutes
- Measures and displays the following international standard formats; ISO 4406, NAS 1638, AS 4059E&F Tables 1 and 2, ISO 11218, GBT 14039, GJB 420B, GOST 17216
- Moisture and temperature sensing
- Data logging and 4000 test result memory
- CMP View software (included on Data stick)
- Bluetooth printer (optional equipment)
- Full accessories kit included
- Work-all-day battery that can handle up to 140 tests on a single charge

Scope of Supply

- 1 x CML4 (Model: CML4W0M001)
- 1 x M16 x 2 Microbore pressure hose, 1500 mm long + pouch
- 1 2000 mm Quick release waste hose + pouch
- 1 x 1L Waste container
- 1 x Power cable and regional adaptors (UK/EU/US/CN/AUS) (Plug type dependent on order specification)
- 1 x USB Stick with digital copies of product user guides, CMP View software, accessory products, drivers and product brochures
- 2 x Hard copy certificate of calibration
- 1 x 1500 mm quick-release offline hose and pouch (Low pressure)
- 1 x USB C to USB A cable

See Accessories at page 93




GENERAL INFORMATION CML4

Technical data

Technology High precision LED light extinction automatic optical contamination monitor

Particle Sizing >4, >6, >14, >21, >25, >38, >50, >70 μm_(c)

Analysis range ISO 4406 NAS 1638 AS4059 Rev E, Table 1 AS4059 Rev E, Table 2 AS4059 Rev F, Table 1 AS4059 Rev F, Table 2 GBT 14039 GJB 420 B GOST 17216

 $\begin{array}{l} \textbf{Accuracy} \\ \pm \ 1/2 \text{ ISO code for 4, 6, 14 } \mu m_{(c)} \\ \pm 1 \text{ code for larger sizes} \end{array}$

Calibration Calibrated with ISOMTD in accordance with ISO 21018 Part 1 and Part 4

Viscosity range Up to 400 cSt

Fluid temperature Minimum: +5 °C Maximum: +80 °C

Ambient Temperature Minimum: -10 °C Maximum: +60 °C

Pressure Offline: Maximum 2.0 bar / 29 psi Online: Maximum 350 bar / 5076 psi Moisture Sensing % RH (Relative Humidity) ±3%

Temperature Measurement ±3 °C

Data Storage Up to 4000 tests

Environmental Protection IP65 (Lid closed) - IP54 (Lid open)

Weight / Dimensions 8.5 kg (unit only) Height 149 mm (not including handle), Depth 155 mm, Width 350 mm

Power Lithium-lon rechargeable battery

Battery Life Up to 8hrs

Software CMP View (Provided)

CML4 is supplied with a full software package and digital product information



FOCUS ON

Exclusive MP Filtri technology

Featuring the latest breakthroughs in LED and photodiode technology, the CML4 delivers outstanding accuracy combined with exceptional repeatability

 $\ensuremath{\textbf{W-Option}}$ Water Saturation level (RH%) and fluid temperature sensor option.

LED light source

A single point high accuracy LED measures particles across all sizes.



Fluid

Photodiodes

Optics

Processor

CMP View Software

Our new CMP View software is used with the LPA3, LPA2 (Aviation Edition), CML2, CML4 and ICM contamination monitors.

When connected to CMP View, MP Filtri CMP devices can transfer results in realtime, or alternatively, historical results can be downloaded from each device's in-built memory.

- Runs on Windows XP, 7, and Windows 10
- Included free with CMP Products
- Brand new design, created in-house for ease of use
- Comprehensive functionality
- Can be mastered quickly without the need for formal training
- Key results and data available at-a-glance
- Full adjustment and control of product settings, test times and alarms
- Easy test report generation
- Full trend analysis
- Universal format across our contamination monitoring product range
- Multi-machine monitoring





CML4

Dimensions



Designation & Ordering code

AUTOMATIC CONTAMINATION MONITOR CML4											
Series	Configuration example:	CML4	W) (М	00	1			
CML4 Light extinction Contamination monitor											
Moisture Sensor											
W With moisture and temperature sensor	-										
Design Reference											
0 Standard option	_										
	_										
Fluid compatibility											
M Mineral oil and synthetic fluids	_										
Design Reference											
00 Standard option with full accessory kit and carry bag	_										
Country Plug Type	1										
1 UK											
2 US	-										
3 EU	-										
4 CN/AUS	-										











ICM 4.0

In-Line Contamination Monitor - WiFi technology integrated





Contamination Monitoring Products

In-Line Contamination Monitor - WiFi technology integrated

The ICM 4.0 automatically measures and displays particulate contamination, moisture and temperature levels in various hydraulic fluids.

It is designed specifically to be mounted directly to systems, where ongoing measurement or analysis is required, and where space and costs are limited.

> Features & Benefits

- Integrated WiFi

- Mobile APP
- 8 channel contamination measurement & display
- Measures and displays the following international standard formats: ISO 4406, NAS 1638, AS 4059E
- Moisture and temperature sensing fluid dependent
- Data logging and 4000 test result memory
- Manual, automatic and remote control flexibility
- Multicolour indicators via LCD (K versions) and LED with output alarm signals as standard
- Robust die cast aluminium construction
- LPA View software (included)
- Pressure max. 420 bar
- Environmental protection IP65/67 versatile
- Secondary connector to allow the simultaneous control/download of results during operation
- 4-20mA analogue output as standard

- Scope of Supply 1 x ICM 4.0 (Specific model will be as per ordered item)
- 1 x 3m Twisted Pair Cable Assembly
- 1 x Hard copy Quick start/wiring installation guide
- 1 x Hard copy Fluid Condition Handbook
- 1 x Digital copy of user guides/software/drivers
- 1 x Hard copy of calibration certificate

See Accessories at page 93

Status LED

All ICM 4.0 versions have a multicolour indicator on the front panel, which is used to indicate the status or alarm state. ICM-K versions also have a screen that changes colour. The alarm thresholds can be set from LPA-View via the serial interface.

Screen and multicolor indicators

- Green indicates that the test result passed, i.e. none of the alarm thresholds were exceeded
- Yellow indicates that the lower cleanliness limit was exceeded, but not the upper one
- Red indicates that the upper clean liness limit was exceeded
- Blue indicates that the upper water content limit was exceeded
- Red/Blue Alternating indicates both cleanliness and water content upper limits exceeded
- Violet indicates that the upper temperature limit was exceeded





Top view

Bottom view



Technical data

Technology LED based Light Extinction Automatic Optical Particle Counter

Particle Sizing >4, 6, 14, 21, 25, 38, 50, 70 μm_(c)

Analysis range ISO 4406 Codes 8 to 24 NAS 1638 Class 2 to 12 AS4059/ISO 11218 Rev E, Table 1 Size Codes 2-12 AS4059/ISO 11218 Rev E, Table 2 Size Codes, A: 000 TO 12, B: 00 to 12, C: 00 to 12, D: 2 to 12, E: 4-12, F: 7 to 12 AS4059 Rev F, Table 1 Size Codes 2-12 AS4059 Rev F, Table 2 Size Codes cpc [000 to 12, 00 to 12, 00 to 12, 2 to 12, 4 to 12, 7 to 12] GBT14039 Codes 8-24 GJB420B Size Codes, A: 000 to 12, B: 00 to 12, C: 00 to 12, D: 2 to 12, E: 4-12, F: 7 to 12 Please Note: Lower Limits are Test Volume dependent

Accuracy

 $\begin{array}{l} \pm \ 1/2 \ ISO \ code \ for \ 4, \ 6, \ 14 \ \mu m_{(c)} \\ \pm 1 \ code \ for \ 21, \ 25, \ 38, \ 50, \ 70 \ \mu m_{(c)} \end{array}$

Calibration Individually calibrated with ISO Medium Test Dust (MTD) based on ISO 11171, on equipment certified by I.F.T.S. ISO 11943

Operating Flow Rate 20 - 400 ml/minute

Viscosity range Up to 1000 cSt

Fluid temperature Minimum: -25 °C Maximum: +80 °C

Ambient Temperature Minimum: -10 °C Maximum: +55 °C

Pressure Minimum: 0.5 bar / 7.25 psi Maximum: 420 bar/ 6092 psi static

Test time Adjustable 10 - 3600 seconds. Factory set to 120 seconds. Start delay & programmable test intervals available as standard

Flow rate measurement Indicator only Moisture Sensing % RH (Relative Humidity) ±3%

Temperature Measurement ±3 °C

Data Storage Up to 4000 tests

Communication options RS485, MODBUS, CANBUS, 4-20mA time multiplex as standard

Relays Two solid state relays fitted to "R" version for output to alarm circuits

Environmental Protection IP 65/67 versatile IK04 Impact Protection

Weight / Dimensions 1.6 kg, Height 123 mm, Depth 65 mm, Width 142 mm

Supply Voltage 9-36VDC

Power consumption <2.2 W

Outer Casing Finish Polyurethane BS X34B. Colour BS381-638 (Dark Sea Grey) Industry 4.0 ready with appropriate accessory product

Wetted parts M - C46400 Cu alloy, 316 stainless steel, FPM, FR4, sapphire. N - 316 stainless steel, FPM, sapphire. S - 316 stainless steel, perfluoro elastomer, sapphire, EPDM.

Software LPA View software (included)

ICM 4.0 is supplied with a full software package and digital product information



14.(

Wifi Connectivity

Wifi connectivity ensures you can access and share real-time data and analysis instantly via a number of different platforms.

- All connections from ICM 4.0: Modbus, Canbus, 4-20mA signal and Switched alarm relay outputs (WiFi replaces the need for the remote connector). Non-WiFi Connections also available.
- Cloud based systems: Capability to connect to customers own cloud-based systems via Modbus. User access to all ICMs on the same network, including remotely via VPN.
- Web browser readouts: Generated from the unique IP address of each ICM 4.0.
- Mobile App: Available for Apple iOS and Android devices.

LPA View Software

The LPA View software is used with the LPA3, LPA2, CML2, CML4 and ICM particle counters. When connected to LPA View, MP Filtri CMPs can transfer results in realtime, or alternatively, historical results can be downloaded from the CMP's inbuilt memory.

- Runs on Windows XP, 7, and Windows 10
- Full adjustment & control of product settings, test times and alarms
- Easy test report generation
- Trend analysis
- Graphical display options
- Universal format across our contamination monitoring product range



Hydraulic Circuit



ICM 4.0

Dimensions



Designation & Ordering code

Seri	es	Configuration example:	ICM	W	Ν	Λ	K	F	ז	G1	4.	0
ICM	In-Line Contamination Monitor								L			_
Mois	sture Sensor (RH%)											
0	Without moisture and temperature sensor											
W	With moisture and temperature sensor	-										
Flui	I compatibility											
М	Mineral/synthetic oils	_										
Ν	Subsea and water based fluids (*)	_										
S	M & N type fluids & phosphate esters/aviation fluids (*) - G3 port option only	-										
Key	ad / Display	L										
0	Without LCD and keypad control	_										
K	With LCD and keypad control	-										
Devi	ce output	L										
R	With relays / external alarm outputs	-										
Con	nections											
G1	M16x2 test points											
G3	1/4"BSPP female ports	-										
G4	7/16th UNF female ports	-										
Seri	95			 								
4 0	ICM / 0 with integral WiFi											

(*) ${\bf N}$ and ${\bf S}$ version, moisture sensor (W) not available







ICM 2.0

In-Line Contamination Monitor





Contamination Monitoring Products

In-Line Contamination Monitor

The ICM 2.0 automatically measures and displays particulate contamination, moisture and temperature levels in various hydraulic fluids.

It is designed specifically to be mounted directly to systems, where ongoing measurement or analysis is required, and where space and costs are limited.

> Features & Benefits

- 8 channel contamination measurement & display
- Measures and displays the following international standard formats: ISO 4406, NAS 1638, AS 4059E
- Moisture and temperature sensing fluid dependent
- Data logging and 4000 test result memory
- Manual, automatic and remote control flexibility
- Multicolour indicators via LCD (K versions) and LED with output alarm signals as standard
- Robust die cast aluminium construction
- LPA View software (included)
- Pressure max. 420 bar
- Environmental protection IP65/67 versatile
- Secondary connector to allow the simultaneous control/download of results during operation
- Option available to download all results onto a USB stick, direct from the ICM
 4-20mA analogue output as standard

Scope of Supply

- 1 x ICM 2.0 (Specific model will be as per ordered item)
- 1 x 3m Twisted Pair Cable Assembly
- 1 x Hard copy Quick start/wiring installation guide
- 1 x Hard copy Fluid Condition Handbook
- 1 x Digital copy of user guides/software/drivers
- 1 x Hard copy of calibration certificate

See Accessories at page 93

Status LED

All ICM 2.0 versions have a multicolour indicator on the front panel, which is used to indicate the status or alarm state. ICM-K versions also have a screen that changes colour. The alarm thresholds can be set from LPA-View via the serial interface.

Screen and multicolor indicators

- Green indicates that the test result passed, i.e. none of the alarm thresholds were exceeded
- Yellow indicates that the lower cleanliness limit was exceeded, but not the upper one
- Red indicates that the upper clean liness limit was exceeded
- Blue indicates that the upper water content limit was exceeded
- Red/Blue Alternating indicates both cleanliness and water content upper limits exceeded
- Violet indicates that the upper temperature limit was exceeded





Technical data

Technology LED Based Light Extinction Automatic Optical Contamination Monitor

Particle Sizing >4, 6, 14, 21, 25, 38, 50, 70 μm_(c)

Analysis range ISO 4406 Codes 8 to 24 NAS 1638 Class 2 to 12 AS4059/ISO 11218 Rev E, Table 1 Size Codes 2-12 AS4059/ISO 11218 Rev E, Table 2 Size Codes, A: 000 TO 12, B: 00 to 12, C: 00 to 12, D: 2 to 12, E: 4-12, F: 7 to 12 AS4059 Rev F, Table 1 Size Codes 2-12 AS4059 Rev F, Table 2 Size Codes cpc [000 to 12, 00 to 12, 00 to 12, 2 to 12, 4 to 12, 7 to 12] GBT14039 Codes 8-24 GJB420B Size Codes, A: 000 to 12, B: 00 to 12, C: 00 to 12, D: 2 to 12, E: 4-12, F: 7 to 12 Please Note: Lower Limits are Test Volume dependent

Accuracy

 $\begin{array}{l} \pm \ 1/2 \ \text{ISO} \ \text{code} \ \text{for} \ 4, \ 6, \ 14 \ \mu\text{m}_{\text{(c)}} \\ \pm 1 \ \text{code} \ \text{for} \ 21, \ 25, \ 38, \ 50, \ 70 \ \mu\text{m}_{\text{(c)}} \end{array}$

Calibration Individually calibrated with ISO Medium Test Dust (MTD) based on ISO 11171, on equipment certified by I.F.T.S. ISO 11943

Operating Flow Rate 20 - 400 ml/minute

Viscosity range Up to 1000 cSt

Fluid temperature Minimum: -25 °C Maximum: +80 °C

Ambient Temperature From -25 °C to +80 °C (non K version) From -25 °C to +55 °C (K version)

Pressure Maximum: 420 bar / 6092 psi

Test time Adjustable 10 - 3600 seconds. Factory set to 120 seconds. Start delay & programmable test intervals available as standard

Flow rate measurement Indicator only Moisture Sensing % RH (Relative Humidity) ±3%

Temperature Measurement ±3 °C

Data Storage Up to 4000 tests

Communication options RS485, MODBUS, CANBUS, 4-20mA time multiplex as standard

Relays Two solid state relays fitted to "R" version for output to alarm circuits

Environmental Protection IP 65/67 versatile IK04 Impact Protection

Weight / Dimensions 1.6 kg, Height 123 mm, Depth 65 mm, Width 142 mm

Supply Voltage 9-36VDC

Power consumption <2.2 W

Outer Casing Finish Polyurethane BS X34B. Colour BS381-638 (Dark Sea Grey) Industry 4.0 ready with appropriate accessory product

Wetted parts M - C46400 Cu alloy, 316 stainless steel, FPM, FR4, sapphire. N - 316 stainless steel, FPM, sapphire. S - 316 stainless steel, perfluoro elastomer, sapphire, EPDM.

Software LPA View software (included)

ICM 2.0 is supplied with a full software package and digital product information



ICM 2.0

LPA View Software

The LPA View software is used with the LPA3, LPA2, CML2, CML4 and ICM particle counters. When connected to LPA View, MP Filtri CMPs can transfer results in realtime, or alternatively, historical results can be downloaded from the CMP's inbuilt memory.

- Runs on Windows XP, 7, and Windows 10
- Full adjustment & control of product settings, test times and alarms
- Easy test report generation
- Trend analysis
- Graphical display options
- Universal format across our contamination monitoring product range



Hydraulic Circuit





ICM 2.0

Dimensions



Designation & Ordering code

	AUTOMATIC PARTIC	LE COUNTER ICM 2	.0						
Seri	98	Configuration example:	ICM	W	Μ	K	R	G1	2.0
ICM	In-Line Contamination Monitor								
Mois	sture Sensor (RH%)								
0	Without moisture and temperature sensor								
W	With moisture and temperature sensor								
Fluid	I compatibility								
	Willeral/Synthetic ons								
N	Subsea fluids and water based fluids (^)								
<u>s</u>	Phosphate ester and aggressive fluids (*)								
Kevi	nad / Display								
0	Without keypad / display								
K	With keypad / display								
	· · · · · · · · · · · · · · · · · · ·								
Devi	ce output								
R	With relays / external alarm outputs								
U	Test record transfer (direct to USB stick) plus relays/external alarm outputs								
Con	nections								
G1	ICM complete with M16x2 pressure test point connections fitted								
G3	1/4" BSP - Female port								
G4	7/16" UNF - Female port								
Serio	98								
2.0									

(*) ${\bf N}$ and ${\bf S}$ version, moisture sensor (W) not available







ATEX Fluid Contamination Monitors

<mark>(Ex</mark>

 $^{\prime}$





Contamination Monitoring Products

(Ex) Atex Zone 2, Cat 3G, Fluid Contamination Monitors

Our AZ2 contamination monitor can automatically measure and save particulate contamination, moisture and temperature levels in various hydraulic fluids. They are designed specifically to be mounted directly to systems where ongoing measurement or analysis is required in high risk or explosive environments.



> Features & Benefits

- 8 channel contamination measurement & display
- Measures and displays the following international standard formats: ISO 4406, NAS 1638, AS 4059E
- RS485, MODBUS, CANBUS
- Moisture and temperature sensing fluid dependent
- Data logging and 4000 test result memory
- Automatic and remote control flexibility
- Multicolour indicators via onboard LED with output alarm signals as standard
- LPA View software (included)

Scope of Supply

- 1 x ICMKAZ2 (*)
- 1 x Atex approved non wired cable connector and gland
- 1 x Hard copy Fluid Condition Handbook
- 1 x Digital copy of user guides/software/drivers
- 1 x Hard copy of calibration certificate
- 1 x Hard copy of atex certificate

(*) Specific model will be as per ordered item

See Accessories at page 93

Status LED

All AZ2 versions have a multicolour indicator on the front panel, which is used to indicate the status or alarm state. The alarm thresholds can be set from LPA-View via the serial interface and bespoke connector (available on request).

Multicolor indicators

- Green indicates that the test result passed, i.e. none of the alarm thresholds were exceeded
- Yellow indicates that the lower cleanliness limit was exceeded, but not the upper one
- Red indicates that the upper clean liness limit was exceeded
- Blue indicates that the upper water content limit was exceeded
- Red/Blue Alternating indicates both cleanliness and water content upper limits exceeded
- Violet indicates that the upper temperature limit was exceeded





Technical data

Technology LED Based Light Extinction Automatic Optical Contamination Monitor

Particle Sizing >4, 6, 14, 21, 25, 38, 50, 70 μm_(c)

Analysis range ISO 4406 Code 0 to 25 NAS 1638 Class 00 to 12 AS4059 Rev. E Table 1&2 Sizes A-F: 000 to 12

Accuracy \pm 1/2 ISO code for 4, 6, 14 µm_(c) \pm 1 code for 21, 25, 38, 50, 70 µm_(c)

Calibration Individually calibrated with ISO Medium Test Dust (MTD) based on ISO 11171, on equivalent certified by I.F.T.S. ISO 11943

Operating Flow Rate 20 - 400 ml/minute

Viscosity range Up to 1000 cSt

Fluid temperature Minimum: -25 °C Maximum: +80 °C

Ambient Temperature Minimum: -25 °C Maximum: +80 °C

Pressure

Maximum: 400 bar / 5802 psi (for high frequency pressure pulse and out range temperature applications contact MP Filtri)

Test time

Adjustable 10 - 3600 seconds. Factory set to 120 seconds. Start delay & programmable test intervals available as standard

Flow rate measurement Indicator only

Moisture Sensing % RH (Relative Humidity) ±3%

Temperature Measurement ±3 °C Data Storage Up to 4000 tests

Communication options RS485, RS232, MODBUS, CANBUS as standard

Relays Two solid state relays fitted to "R" version for output to alarm circuits

Environmental Protection

Weight / Dimensions 10.5 kg, Height 320 mm, Depth 130 mm, Width 186 mm

Supply Voltage 9-36VDC

Current Supply 12V - 150mA 24V - 80mA 36V - 60mA

Power consumption <2.2 W

Outer Casing Finish Stainless Steel

Wetted parts

- M C46400 Cu alloy, 316 stainless steel, FPM, FR4, sapphire.
- N 316 stainless steel, FPM, sapphire.
- S 316 stainless steel, perfluoro elastomer, sapphire, EPDM.

Software LPA View software (included)

Atex classification CE 😔 3 G EX nR IIB T5 GC IP66

ICM AZ2 cable wiring details

MP Filtri do not supply an ATEX approved cable with the ICM AZ2 products as customers may run such cables through varying ATEX zones. Wiring diagrams supplied, please consult product user guide for full information.

Note: an adapter cable and ICMUSBi product will be required should LPA View be utilised as the control software. These accessories are only suitable for use outside of the zoned areas

AZ2 is supplied with a full software package and digital product information



AZ2

Dimensions



Designation & Ordering code

AUTOMATIC PARTICLE COUNTER AZZ
Configurations :
ICM W M K R G1 AZ2 Moisture Sensor, Mineral / Petroleum based fluids, LCD Display, Relays, M16x2 test point connections
ICM 0 M K R G1 AZ2 Mineral / Petroleum based fluids, LCD Display, Relays, M16x2 test point connections
ICM 0 N K G1 AZ2 Off shore / Water based fluids, LCD Display, Relays, M16x2 test point connections
ICM O S K R G1 AZ2 Phosphate Ester and aggressive fluids, LCD output, Relays, M16x2 test point connections

All of MP Filtri's AZ2 products are designed to be run via PLC control & the Modbus communication protocol. Note: All units are fully compatible with and can be programmed via our bespoke windows based LPA View software.











In-line Contamination Monitoring Unit







Contamination Monitoring Products

In-line Contamination Monitoring Unit

The ICU automatically measures particulate contamination levels in various hydraulic fluids and is designed for industrial applications.

It is designed to be manifold mounted directly to systems, where ongoing measurement or analysis is required, and where space and costs are limited.

> Features & Benefits

- Manifold mounting
- 3 channel contamination measurement
- Measures ISO 4406
- Robust design and construction
- Pressure max. 350 bar
- Environmental protection IP65/67 versatile
- 4-20mA analogue output as standard

Scope of Supply

- 1 x ICU0M00G5P01
- 1 x Installation kit: 4 x M6x1.0x60 mm long fixing bolts
 - $2 \times 6.50 \text{ ID } \times 1.5 \text{ CSD FKM o-ring seals}$
- 1 x Hard copy of calibration certificate



Right facing view



Front / Left facing view







Technical data

Technology LED Based Light Extinction Automatic Optical Contamination Monitor

Particle Sizing $>4, 6, 14 \ \mu m_{(c)}$

Analysis range ISO 4406 Code 0 to 20

Accuracy \pm 1/2 ISO code for 4, 6, 14 $\mu m_{(c)}$ across the analysis range

Calibration Individually calibrated with ISO Medium Test Dust (MTD) based on ISO 11171, on equipment certified by I.F.T.S. ISO 11943

Operating Flow Rate 200 ml/minute controlled by the built in flow control valve

Viscosity range Up to 1000 cSt

Fluid temperature Minimum: 0 °C Maximum: +80 °C

Ambient Temperature Minimum: 0 °C Maximum: +60 °C

Pressure Minimum: 25 bar / 362 psi Maximum: 350 bar / 5075 psi

Test time Adjustable 10 - 3600 seconds **Communication options** 4-20 mA time multiplex as standard

Environmental Protection IP 65/67 versatile

Weight / Dimensions 1.4 Kg, Height 70 mm, Depth 50 mm, Width 93 mm

Supply Voltage 24VDC ± 20%

Power consumption <2.2 W

CableElectrical cable has to be ordered separately (optional accessory),MP Filtri item no. 13.061000 - ICU Cable M12 4 pin 1.5m long

ICU is supplied with a full software package and digital product information



Dimensions



Contamination Monitoring Products (60)



Designation & Ordering code

AUTOMATIC PARTICLE COUNTER ICU

Configurations :



Without moisture sensor, Mineral oil, Without keypad/display, 4 to 20mA timed multiplex, Manifold mounted, Standard option

Customized version









ACMU

Auxiliary Contamination Monitoring Unit







Contamination Monitoring Products

Auxiliary Contamination Monitoring Unit

Incorporating the ICM, the ACMU is specifically designed for aerated, viscous and/or un-pressurized hydraulic/lubrication systems.

Where can it be used?

- Wind/Tidal/Wave Energy
- Gearbox applications
- Gearbox monitoring
- Offshore & ship systems
- Lubrication & Oil systems
- Mobile Equipment
- Test Benches

When should it be used?

- Entrained air or turbulent flows
- Higher viscosity fluids
- Unpressurized systems

Why should it be used?

- Easy to retro-fit
- Exceptional communication & 4000 test memory
- Reliable & accurate performance

Available versions:

- Cabinet version
- Plate version



Closed Cabinet version Front/Right facing view

Scope of supply

- 1 x ACMU (Specific model will be as per ordered item, 1/4" BSP inlet/outlet ports as standard)
- 1 x 3m Twisted Pair Cable Assembly (Plate version)
- 1 x 5m length twisted pair cable (Cabinet version)
- 2 x 1/4" BSP to 7/16 JIC coupling
- 1 x Hard copy Quick start/wiring installation guide
- 1 x Hard copy Fluid Condition Handbook
- 1 x Digital copy of user guides/software/drivers
- 1 x Hard copy of calibration certificate

See Accessories at page 93

Hydraulic Hoses (External) Customer to source their own

Re-calibration Defined by customer Quality Controls recommended 1 year



Open Cabinet version Front facing view



Plate version Front facing view



GENERAL INFORMATION ACMU

Technical data

In-Line contamination monitor ICM with keypad and backlit display and relays

Analysis Range ISO 4406 Codes 8 to 24 NAS 1638 Class 2 to 12 AS4059/ISO 11218 Rev E, Table 1 Size Codes 2-12 AS4059/ISO 11218 Rev E, Table 2 Size Codes, A: 000 TO 12, B: 00 to 12, C: 00 to 12, D: 2 to 12, E: 4-12, F: 7 to 12 AS4059 Rev F, Table 1 Size Codes 2-12 AS4059 Rev F, Table 2 Size Codes cpc [000 to 12, 00 to 12, 00 to 12, 2 to 12, 4 to 12, 7 to 12] GBT14039 Codes 8-24 GJB420B Size Codes, A: 000 to 12, B: 00 to 12, C: 00 to 12, D: 2 to 12, E: 4-12, F: 7 to 12 Please Note: Lower Limits are Test Volume dependent

Fluid Compatibility / Corrosion Resistance Hydrocarbon based & Synthetic hydraulic fluids

Circuit Flow Rate 40 ml/min to 400 ml/min

Viscosity range Max. 1000 cSt - Min. 10 cSt

Communication Options PLC compatible. RS485, RS232 & CanBus (J1939 typical)

Fluid Temperature (Start Up) Minimum: Viscosity dependant. Not greater than 1000 cSt Maximum: +80 °C

Fluid Temperature (Continuous) Minimum: Viscosity dependant. Not greater than 1000 cSt Maximum: +80 °C

Ambient Temperature (Start Up) Minimum: -40 °C Maximum: +50 °C Inlet Pressure Min. Positive pressure Max. 50 bar / 725 psi gauge pressure (pump option dependant)

Outlet Pressure Min. Atmosphere (1013 bar at sea level) Max. 3.0 bar / 43.5 psi (gauge pressure)

Moisture Sensing (RH%) Available with or without moisture sensor

Weight 21 Kg (cabinet version) - 13 Kg (plate version)

Dimensions Cabinet version: Height 562 mm, Depth 226 mm, Width 482 mm Plate version: Height 410 mm, Depth 186 mm, Width 395 mm

Electric Motor 110V AC, 230V AC, 415V AC, 690V AC

Power Consumption 0.25 kW max

USBi Comms Junction Box See USBi user guide - cabinet version No junction box - plate version Industry 4.0 ready with appropriate accessory product

ACMU is supplied with a full software package and digital product information



LPA View Software

The LPA View software is used with the LPA3, LPA2, CML2, CML4 and ICM particle counters. When connected to LPA View, MP Filtri CMPs can transfer results in realtime, or alternatively, historical results can be downloaded from the CMP's inbuilt memory.

- Runs on Windows XP, 7, and Windows 10
- Full adjustment & control of product settings, test times and alarms
- Easy test report generation
- Trend analysis
- Graphical display options
- Universal format across our contamination monitoring product range



Type of applications



(*) Gauge pressure

Designation & Ordering code

AUTOMATIC PARTICLE COUNTER ACMU											
Series		Configuration example:	ACMU	W		D	С		S	230V	
ACMU											
Moistu	re Sensor (RH%)										
0	Without moisture and temperature sensor										
W	With moisture and temperature sensor										
Pressu	re Sensor										
D	Up to 50 bar inlet (gauge pressure), atmosphere outlet										
В	0.5 bar (gauge pressure) {1.0 bar max inlet}, 3.0 bar (gauge pressure) max	a <u>x</u> outlet									
Туре											
C	Cabinet version (supplied with 5 metre communication lead)										
Ρ	Plate mounted version (supplied with ICM 3 metre cable)	_									
Versio	1										
S	Standard version								_		
Motor	option										
110V	110V Motor (Dual frequency 50Hz/60Hz, single phase)										
230V	230V Motor (single phase)										
400V	400V Motor (3 phase)										
690V	690V Motor (3 phase)										



Dimensions















BS110 & BS500

Bottle Samplers - For use with MP Filtri's portable APC





Contamination Monitoring Products

Bottle Samplers

The 110 ml bottle samplers are suitable for off-line and laboratory applications where fluid sampling at point of use is inaccessible or impractical.

A fluid de-aeration facility comes as standard.

> Features & Benefits

- Vacuum feature for de-aeration of fluids
- Compatible with all portable MP Filtri Contamination Monitoring Products - Strong Laboratory aesthetic
- Transparent outer for visual indication
- Full accessories kit included
- Includes carry case (BS110)
- Contact MP Filtri for use with fluids other than those stated

Scope of Supply

- 1 x 110 ml Bottle Sampling unit

- 1 x Pressure cap
- 1 x Vacuum cap
- 1 x M16x2 microbore pressure hose, 600 mm long
- 1 x 1L waste receptacle
- 1 x 12V, 2A power adapter c/w UK/EU/US/AUS/CN heads
- 1 x pack of disposable dip tubes
- 1 x hand pump
- 1 x length of hose for hand pump
- 3 x 100 ml clear plastic bottles
- 1 x Hard copy of product user guide
- 1 x Digital copy of user guides/software/drivers
- 2 x Thermal printer paper
- 1 x Carry case

See Accessories at page 93



Front facing view



Left facing view



Open case Front facing view


GENERAL INFORMATION BS110

Technical data

Max. Chamber Pressure 2.5 bar / 36.3 psi only

Min. Chamber Pressure 0.61 bar / 8.85 psi to 0.81 bar / 11.75 psi

For use with.... MP Filtri Portable Contamination Monitoring Products

Supply Voltage 12V, 2 amp

Wetted Parts (Internal) Aluminium HE30, 303 Stainless Steel, Polyurethane, FPM, Acrylic

On/Off & Stop/Start signals Switch (Manual Operation)

Hydraulic Hoses (External) 600 mm x 2 mm ID M16x2 microbore pressure hose

Max Flow Rate (ml/min) Viscosity dependant

Min Flow Rate (ml/min) Viscosity dependant

Visual Pressure Indicator No

Weight / Dimensions 7 kg, Height 212 mm, Depth 163 mm, Width 130 mm

Pressure Gauge No

Pressure Ranges 2.0 bar / 29 psi options

IP Rating IP50 Fluid Compatibility / Corrosion Resistance Industrial Hydrocarbon based fluids (typical)

Min Outlet Pressure 1013 bar / 14.7 psi

Max. Fluid Temperature (Continuous) 80 °C / 176 °F

Min Fluid Temperature Viscosity dependant

Max. Viscosity 400 cSt

Min. Viscosity 1 cSt

Max outlet pressure 2.0 bar / 29 psi options

Min. Continuous Ambient Temperature 10 °C / 50 °F

Max. Continuous Ambient Temperature 55 °C / 131 °F

Power Consumption 24W

Warranty 12 months

Installation Indoor Use / Laboratory Use





BS110 Bottle Samplers

Dimensions



Designation & Ordering code

	BOTTL	E SAMPLER BS110				
Series		Configuration example:	BS110	Μ) [0
BS110	110 ml fluid volume					
Fluid co	mpatibility	L				
М	Mineral oil and synthetic fluids					
Pressur	e rating	L				
0	2.0 bar					
Pressur	e cylinder option	L				
0	Acrylic cylinder assembly					





Description

Contamination Monitoring Products

Bottle Samplers

The 500 ml bottle samplers are suitable for off-line and laboratory applications where fluid sampling at point of use is inaccessible or impractical.

A fluid de-aeration facility comes as standard.

> Features & Benefits

- Vacuum feature for de-aeration of fluids
- Compatible with all portable MP Filtri Contamination Monitoring Products - Strong Laboratory aesthetic
- Transparent outer for visual indication
- Full accessories kit included
- Contact MP Filtri for use with fluids other than those stated

Scope of Supply

- 1 x 500 ml Bottle Sampling base unit (*)
- 1 x Top cap, pressure/vacuum chamber (*)
- 1 x M16x2 microbore pressure hose, 600 mm long
- 1 x Power adapter
- 1 x UK/EU/US/AUS/CN power lead*
- 3 x 210 ml clear glass bottles
- 2 x 500 ml clear glass bottles
- 1 x Digital copy of user guides/software/drivers

(*) Specific model will be as per ordered item

See Accessories at page 93



Front / Right facing view



Back / Left facing view



Front / Left facing view



Back / Right facing view



GENERAL INFORMATION BS50C

Technical data

Max. Chamber Pressure 2.5 bar / 36.3 psi (standard), 4.5 bar / 65.3 psi (high pressure)

Min. Chamber Pressure 0.61 bar / 8.85 psi to 0.81 bar / 11.75 psi

For use with.... MP Filtri Portable Contamination Monitoring Products

Supply Voltage 12V, 5 amp

Wetted Parts (Internal) Aluminium 6082 T6, 303 Stainless Steel, 316 Stainless Steel. Seal & Cylinder material optional

On/Off & Stop/Start signals Switch (Manual Operation)

Hydraulic Hoses (External) 600 mm x 2 mm ID M16x2 microbore pressure hose

Max Flow Rate (ml/min) Viscosity dependant

Min Flow Rate (ml/min) Viscosity dependant

Visual Pressure Indicator Yes

Weight / Dimensions 9 kg, Height 333 mm, Depth 341 mm, Width 264 mm

Pressure Gauge Yes (only on 4.5 bar / 65.3 psi version)

Pressure Ranges 4.5 bar / 65.3 psi or 2.5 bar / 36.3 psi options

IP Rating IP50 Fluid Compatibility / Corrosion Resistance Industrial, aerospace & off-shore control fluids (typical)

Min Outlet Pressure 1013 bar / 14.7 psi

Max. Fluid Temperature (Continuous) 80 °C / 176 °F

Min Fluid Temperature Viscosity dependant

Max. Viscosity Not greater than 400cSt (on 2.5 bar version)

Min. Viscosity 1 cSt

Max outlet pressure Version dependant: 2.5 bar / 36.3 psi for 0 version 4.5 bar / 65.3 psi for H version

Min. Continuous Ambient Temperature 10 °C / 50 °F

Max. Continuous Ambient Temperature 55 °C / 131 °F

Power Consumption 60W

Warranty 12 months

Installation Indoor Use / Laboratory Use





BS500 Bottle Samplers

Dimensions



Designation & Ordering code

	BOTTLI	E SAMPLER B	\$500							
Serie <u>s</u>			Configuration exa	mple:	BS500	V	() [0	UK
BS500	500 ml fluid volume	_								
Fluid co	ompatibility									
V	Mineral oil and synthetic fluids, Subsea and water based fluids	_								
E	Phosphate ester and aggressive fluids									
S	Phosphate ester and aggressive fluids, Mineral oil and synthetic fluids, Subsea and water based fluids	_								
Pressu	re rating									
0	2.0 bar, standard option	_								
H	4.0 bar, high pressure option (*)	_								
Pressu	re cylinder option									
0	Acrylic cylinder assembly	_								
S	Glass cylinder assenbly (**)	_								
Power	adapter options									
UK	UK power adapter									
EU	European power adapter									
US	USA power adapter									
AU/CN	Australasia power adapter	_								
(*) 11										

(*) = H version only available in BS500 V version

 $(^{\star\star})$ = Glass version only available in BS500 E & S version





HOW SAMPLING

Bottles



At MP Filtri we offer a range of standard & ultra-clean glass bottles for your sampling needs:

100 ml, 210 ml & 500 ml Standard Bottles (not certified clean)

- 100 ml, available in amber glass or clear plastic varieties
- 210 ml, available in clear glass
- 500 ml, available in clear glass

100 ml & 210 ml Ultra Clean Glass Bottles

- Certified to ISO 3722 Hydraulic fluid power
- Fluid sample containers
- Qualifying and controlling cleaning methods NAS 0 to NAS 00/ AS4059E Table 1 Class 0

Glass Colour

Clear glass provides better visibility of the sample, making de-aeration easier to monitor. Amber glass may reduce the effect of UV light on the sample, reducing the risk of microbial growth and FAME (fatty acid methyl esters) which can be significant in fuel analysis.

DE-AERATION & CLEANLINESS

Samples should be shaken vigorously before use however this causes the sample to become aerated which means leaving it to settle.

The BS500 & BS110 de-aeration facility reduces this settling time, allowing more samples to be analysed thereby increasing productivity.



SAMPLING FACTORS

Below are some of the factors which should be considered when taking a sample. For guidance on sampling procedures refer to ISO 4021 & the product user guide.

- Location of the take-off point
- Homogeneity of the sample
- Local area cleanliness
- Bottle cleanliness
- Equipment cleanliness
- Flushing / Cleaning fluid cleanliness
- Operator clothing & cleanliness Air cleanliness

100 μm Dust particle (dead skin)



40 μm Pollen



24 μm White blood cell



10 µm

Dust mite faeces



8 µm

Red blood cell



3 μm E-coli bacteria



HOW SAMPLING

Sample pumps

Hand pump

The pump and its associated parts are also available as a spares. See spares list page 88-89 For systems where there is no practical access to a test point, a sample may need to be taken from an un-pressurized reservoir.

For this occurrence we offer a simple **hand pump device** with both off-line sampling products which provides for clean and efficient sampling.

The design ensures that only the hose is in contact with the sample fluid, providing greater confidence in analysis, and we provide a range of adapters to suit our various bottle sizes.

The pump can be fully dismantled for cleaning and the sample hose plus main seal can be replaced to further improve clean practise.

Ultra clean bottles cleaned to and in accordance with DIN/ISO 5884.

Ultra clean bottles cleanliness verified to ISO 3722.

NAS 1638 cleanliness certification of between Class 00 and Class 0.

Descriptions	Part Code	Dimensions (mm)
100 ml - Ultra Clean Bottle (Certified)	P.02	Ø 50x92
100 ml - Standard Bottle Brown Glass	BS0016	Ø 50x91
100 ml - Clear Plastic Bottle	7.111	Ø 51x92
100 ml - Standard Bottle Tray (72 bottles)	BS0072	N/A
210 ml - Ultra Clean Bottle (Certified)	P.03	Ø 65x130
210 ml - Standard Bottle	8.054	Ø 65x122
500 ml - Standard Bottle	8.328	Ø 82x152

How it works



inside the bottle, syphoning fluid from the reservoir.



The design of the pump means that only the hose is in contact with the fluid protecting the quality of the sample.



The sample level should always finish below the level of the hose. The bottle can now be removed and capped.

Electric vacuum pump









PIK - Patch Imaging Kit

Patch Sampling and Digital Imaging Kit





Description

Contamination Monitoring Products

High-resolution microscopic visual analysis of contamination in fluids

> Features & Benefits

MP Filtri's new Patch Imaging Kit enables sample-testing of fluids, followed by a full analysis of the contaminants - not only recording and measuring the size and shape of particles under magnification (up to 400x) - but also delivers recording and storage of data and results to your laptop or PC.

Rugged and robust yet perfectly portable, the new Patch Imaging Kit enables fast and accurate testing outside the laboratory.

KEY FEATURES

- High-performance digital microscope, enabling magnification up to 400x
- Sophisticated software enables the measurement and analysis of individual particles
- Full patch testing kit apparatus making it easy to take samples quickly and accurately
- Windows-based software for problem-free installation onto PCs and laptops
- Easy to use without the need for formal training
- Heavy-duty peli-case and laser-cut foam surround for maximum protection and portability
- Simple, step-by-step instructional videos
- Perfectly complements MP Filtri's acclaimed range of portable particle counter products

KIT COMPOSITION

- Heavy-duty orange pelicase
- Pelicase foam insert
- Self-adhesive patch test covers
- Patch test membranes -1.2 μm
- Spray bottle
- 2 x Stainless steel tweezers
- Hand-pump
- Waste bottle
- 3 x Clean bottles
- Reusable Nalgene filter assembly
- 0.01mm Calibration slides
- Microscope power adaptor
- USB Data stick (includes microscope software and PDF manual)
- Hose pouch
- 1 x Hose 8 x 6 mm Nalgene vacuum cable
- 1 x Hose 6 x 4 mm Hand pump sampling cable
- Swift Microscope SW150 and accessories including cable and viewer
- Microscope camera 1.3MP
- Serial plate for patch imaging kit
- A5 document wallet
- Patch test report cards
- Optional Electric Vacuum Pump (see page 90)

See Accessories at page 93

(*) pour plus de renseignements, veuillez contacter votre équipe de ventes MP Filtri locale

PRINCIPAL COMPONENTS TECHNICAL DATA

Microscope:

- Digital microscope that connects direct to PC/laptop
- Fully rotatable monocular head for easy shared use, perfect for laboratories and one-on-one instruction
- Available magnification settings of 40X, 100X and 400X
- A dual-illumination system allows examination of both transparent and solid specimens while cool LED lights protect eyesight
- Sleek design with metal carrying handle and base combine with cordless capability to make this microscope practical for field experiments
- The digital microscope allows operators to examine and easily determine the nature and sizes of solid particles inside the fluid.

PARTICLES QUANTITATIVE ANALYSIS

After determination of the nature (and sizes) of particles inside the fluid, it is useful to quantify the contamination inside system.

Determination of quantitative contamination is done by taking fluid sample from the system (preferably in working conditions) and following the sample fluid analysis with an automated particle counter or with a portable particle counter that is linked directly to the system.

They give immediate results according to standard ISO 4406 or NAS 1638. Both particle counters, portable or not, have values and counter indications. Please note the portable particle counters need a minimum pressure to work correctly. They produce immediate results.

Technical data

Sampling Hand pump Optional Electric Vacuum Pump

Patch test Patch test membranes -1.2 μm

Digital analysis Swift Microscope SW150 and accessories including cable and viewer. Microscope camera - 1.3MP Easy-View software for digital analysis

Samples Filtration System Reusable Nalgene filter assembly Waste bottle 3 x Clean bottles Spray bottle

Accessories for identification and test report Patch test report cards 0.01 mm Calibration slides Self-adhesive patch test covers **Rigid carrying case** Heavy-duty orange Pelicase

Weight and dimensions 12.5 kg, Height 265 mm, Depth 390 mm, Width 519 mm



Designation & Ordering code

	PIK - I	PATCH IMAGING KIT	
Produ	ct	Configuration example: PIK	P01
PIK	Patch Imaging Kit	_	
Pump	and Electric supply options		
P01	Hand pump only		
P02	Electric Vacuum Pump - UK supply		
P03	Electric Vacuum Pump - EU supply	—	
P04	Electric Vacuum Pump - US supply		
P05	Electric Vacuum Pump - AUS/CN supply	—	

FLUID COMPATIBILITY CHARTS

HYDROCARBON AND SYNTHETIC

Fluid type	Fluid spec.	ICM		LPA			CML				BS110	S110 BS5					
		Μ	(W)	N	S	М	(W)	N	S	Μ	(W)	N	S	М	V	Е	S
	AEROSHELL FLUID 31 (OX-19)																
	AEROSHELL FLUID 51																
	AEROSHELL FLUID 602																
	CASTROL CONSTAB PS 10W-40																
	DIESEL CALIBRATION OIL 4113																
	FINA POLYGLYCOL FLUID																
	GEAROIL ISO VG 320																
	ISO 32																
	ISO 46																
	ISO 68																
	MIL-H-5606																
	MIL-H-83282																
	MIL-H-87257																
	MOBILGEAR SHC XMP 320																
	NATO H-515 (OM-15)																
SYNTHETIC OR MINERAL	NATO H-520 (OM-18)																
BASED LIQUIDS	NATO H-537																
	RENOLIN PG 68																
	RENOLIN PG 100																
	RENOLIN PG 150																
	RENOLIN PG 220																
	RENOLIN PG 320																
	RENOLIN PG 460																
	RENOLIN PG 680																
	RENOLIN PG 1000																
	RENOLIN UNISYN OL 32																
	RENOLIN UNISYN OL 46																
	RENOLIN UNISYN OL 68																
	RENOLIN UNISYN OL 100																
	RENOLIN UNISYN OL 150																
	STATOIL HYDRAULIC 131																
	AERO HF585B																
	MOBIL DTE 25																
For special applications or for Alternatively, visit the services	fluids not mentioned in this table, p section of our website where we ba	lease ave de	contac	ct MP	Filtri 1 testi	Techn na an	ical ar d anal	nd Sal	es De	partm	ent.				Compa	ıtible mnatik	ole

Not compatible Contact MP Filtri

Typically conductive fluids are not compatible with the moisture sensor.

For guidance on moisture sensing compatibility, contact MP Filtri Technical and Sales Department.

Please note that compatibility is based product performance with fluid viscosity at 20 °C in standard dye colourant or natural state. Tests are conducted with the suitable fluid in its pure state. Performance of solutions or mixed emulsions cannot be guaranteed. "Compatibility" is defined as a liquid which does not suffer short or long term degradation as a result of coming into contact with the wetted materials contained within the product. It is also a confirmation that the transparency of the liquid is suitable for the sensitivity of the product range.

For details on the specific product code required for your fluid, contact contact MP Filtri Technical and Sales Department.

FLUID COMPATIBILITY CHARTS

OFFSHORE	
----------	--

Fluid type	Fluid spec.	ICM			LF	PA			CI	٨L		BS110	BS110 BS		S500		
		М	(W)	N	S	М	(W)	Ν	S	Μ	(W)	Ν	S	М	V	E	S
	HW443																
	HW443R																
	HW453																
	HW540																
	HW540																
	PELAGIC 50																
	PELAGIC 100																
OFFSHORE	TRANSAQUA HT																
& SELECTED WATER BASED	TRANSAQUA HT2																
FLUIDS	FRESH WATER																
	DE-IONISED WATER																
	SEAWATER																
	HOUGHTO-SAFE 273 CTF																
	HOUGHTO-SAFE BC24046																
-	WATER GLYCOL HFC 46																
	LF2100 (99%WATER, 1% MIX)																
	SV3																

AGGRESSIVE FLUIDS





FLUID COMPATIBILITY CHARTS

FUELS

Fluid type	Fluid spec.	ICM			LPA					CI	٨L		BS110	BS50)	
		М	(W)	Ν	S	Μ	(W)	Ν	S	Μ	(W)	N	S	М	V	E	S
	JET A-1																
	JET A																
	JET B																
	JP1																
	JP5																
FUELS	JP6																
	JP7																
	JP8																
	JPTS																
	FT JET FUEL																
	GTL JET FUEL BLEND																
	DIESELS																

BIO FLUIDS

Fluid type	Fluid spec.		IC	M		LPA			CML				BS110	BS500			
		М	(W)	Ν	S	М	(W)	Ν	S	Μ	(W)	Ν	S	М	V	E	S
	BIO-ETHANOL																
	BIO-DIESEL																
	PLANTOHYD N SERIES																
BIODEGRADEABLE FLUIDS	PANOLIN HLP SYNTH 22																
& VEGETABLE OILS	SUNFLOWER OIL																
	RAPESEED OIL																
	CORN OIL																
	GROUND NUT OIL																
	CAT BIO HYDO HEES																
															Contac	t MP I	Filtri
For special applications or for Alternatively, visit the services For guidance on moisture sens Typically conductive fluids are	fluids not mentioned in this table, pl section of our website where we ha sing compatibility, contact MP Filtri 1 not compatible with the moisture se	ease ve de Techni ensor.	conta tails c ical ar	ct MP In fluic Ind Sali	Filtri 1 d testi es Dej	Techni ng an partm	ical ar d anal ent.	nd Sal lysis.	es De	partm	ient.						
Please note that compatibility is based product performance with fluid viscosity at 20 °C in standard dye colourant or natural state. Tests are conducted with the suitable fluid in its pure state. Performance of solutions or mixed emulsions cannot be guaranteed. "Compatibility" is defined as a liquid which does not suffer short or long term degradation as a result of coming into contact with the wetted materials contained within the product. It is also a confirmation that the transparency of the liquid is suitable for the sensitivity of the product range.																	

For details on the specific product code required for your fluid, contact contact MP Filtri Technical and Sales Department.





SPARE PARTS LIST

Description (product types)	Ordering Code
Calibration Verification Fluid (requires use of Bottle Sampling device)	PCCF
CMP Hydraulic connections / options:	
M16x2 microbore pressure hose. plated steel. 600 mm (M versions)	95.Y30Y30X261060
M16x2 microbore pressure hose. plated steel. 1500 mm (M versions)	95.Y30Y30X261150
M16x2 microbore pressure hose. stainless steel. 600 mm (N versions)	95.Y30Y30X161060
M16x2 microbore pressure hose. stainless steel. 1500 mm (N versions)	95.Y30Y30X161150
Waste Hose (M versions). 2000 mm - Brass / FKM	SK0014S30
Waste Hose (N versions). 2000 mm - Stainless Steel / FKM	SK0014S30N
Waste Hose (S versions). 2000 mm - Stainless Steel / FFKM	SK0014S30S
Offline Hose Assembly	481.027000
Pouch for pressure hose/waste hose	7.106
M16x2 M to F Coarse Screen Filter (M and N versions)	SK0040
G1/4 F to F coarse screen filter (M/N/S versions)	11.615
M16x2 F to F Coarse Screen Filter (S versions)	SK0041
Airbus adaptor with test point	SKAA02
Waste Bottle:	
1 Litre - Round	SK0012
1 Litre - Square (for use with CB0001)	SK0013
Communications:	
Serial cable to USB converter	SK0026
PC Download cable	6.123
USB A-B cable	11.081
Bluetooth Portable Printer	482.016000
1m USB A to C Cable	443.074000
ICMKAZ2 to USBi conversion kit - not to be used in zoned areas	11.645
USB stick with all user guides and LPA-View Software	13.055001
Offline sampling equipment:	
Disposable Dip tubes - pack of 50	BS0018
Hand Pump	BS0020
Hand Pump Hose - 1000 mm	BS0022
Bottle Sampler hand pump and hose kit	BS0024
100 ml Standard Brown Glass Bottle	BS0016
Tray of 72 x 100 ml Standard Brown Glass Bottles	BS0072
100 ml Clear Plastic Bottle	7.111
Box of 20 x 100 ml Clear Plastic Bottles	7.112
250 ml Standard Clear Glass Bottle	8.054
Box of 20 x 250 ml Standard Clear Glass Bottles	8.054-20
500 ml Standard Clear Glass Bottle	8.328
DIN/IS05584/IS03722 certiified clean. 100 ml clear glass bottle	P.02
DIN/IS05584/IS03722 certiified clean. 100 ml clear glass bottle - Box of 25	P.0225
DIN/IS05584/IS03722 certiified clean. 250 ml clear glass bottle	P.03
DIN/IS05584/IS03722 certiified clean. 250 ml clear glass bottle - Box of 25	P.0320

SPARE PARTS LIST

I PA2	I PA3	CMI 2	CMI 4	ICM 4 0	ICM 2 0	Ις.Μκα72	ACMU	PIK	BS110	B\$500	ICMUSBi
		OINEE					Aomo		Donto	Decou	Топпосовт
•	•	-	•						•	•	
•	•	•	•	•	•	•			•	•	
•	•	•	•	•	•	•					
•			-		•				•	•	
•		•	-	•	•	-			•	•	
•	•	•	•	•	•	•					
•	•	•	•								
•	•	•									
•	•	•									
			•								
•	•		•					•			
•	•	•	•			•					
				•	•						
•											
•	•	•	•			•					
•											
	•	•							•		
•	•		•								
			-								
•		•									
•		•									
	•										•
			•								
			•								-
						•					•
•	•	•	•	•	•	•	•	•	•	•	•
•											
•	•										
-											
•	•										
•	•										
•	•										
•	•										
•	•										
•	•										
	•										
	•										
	•										
•	•										
•											
•	-										
	•										
	•										



Description (product types)	Ordering Code
Power Options:	
12V. 2A Power Adapter - UK/EU/US/CN/AUS	6.209
19V. 3A Power Adapter	61.034000
12V. 5A Power Adapter for 500 ml Bottle Sampler	8.029
UK Lead for 8.029	8.031
EU Lead for 8.029	8.032
US Lead for 8.029	8.030
CN/AUS Lead for 8.029	8.072
Other:	
Thermal printer paper 57x33 mm	63.083000
Thermal paper roll 57x51 mm	6.160
LPA2 Aviation Edition travel case without foam	TC0005
Replacement foam insert for TC0005	6.300
Heavy-duty orange pelicase	443.061E20
Pelicase foam insert	443.062020
Self-adhesive patch test covers	444.029001
Patch test membranes - 1.2 micron filter	444.010000
Spray bottle	444.018J10
Stainless steel tweezers	444.011120
Waste bottle	444.032J00
Reuseable Nalgene filter assembly	444.024000
0.01 mm Calibration slides	444.025000
Microscope power adaptor	444.033000
Hose - 8 x 6 mm Nalgene vacuum cable	444.026000
Hose - 6 x 4 mm Hand pump sampling cable	7.107
Microscope camera - 1.3 MP	444.016010
Serial plate for patch imaging kit	484.314000
A5 document wallet	444.027001
Patch test report card	444.028001
Electric vacuum pump	444.009000
CML Carry Bag	10.011
LPA3 Carry Bag	63.088000
LPA2 Carry Bag	CB0001
Black support case (without contents)	BS0040
Heavy Duty Travel Case for Bottle Sampler	TC00055B

SPARE PARTS LIST

LPA2	LPA3	CML2	CML4	ICM 4.0	ICM 2.0	ICMKAZ2	ACMU	PIK	BS110	B\$500	ICMUSBi
•		•							•		•
	•		•								
										•	
	•		•							•	
	•		•							•	
	•		•							•	
	•		•							•	
	•		•								
 •											
•											
•											
								•			
								•			
								•			
								•			
								•			
								•			
								•			
								•			
								•			
								•			
								•			
								•			
								•			
								•			
								•			
								•			
		•	•								
	•										
•											
										•	
											•









Accessories



Description

Remote Display Unit

Depending on your application, access and visibility of particle counting equipment can sometimes be an issue. The ICM-RDU has specially been developed to dovetail with its parent ICM 2.0. So you have the option to control and monitor the ICM 2.0 remotely. Supplied with a 10m cable as standard.

> Features & Benefits

- Large backlit display
- Keypad interface
- Robust die-cast aluminium construction
- **Scope of Supply**
- 1 x ICMRDU2.0
- 1 x 10m Twisted Pair Cable Assembly
- 1 x Digital copy of user guides/software/drivers



Dimensions





Designation & Ordering code





ACCESSORIES

444.009000

ICM-F

Description

Electric Vacuum Pump MP Filtri's Patch Imaging Kit is available with an optional electric pump (spares number: 444.009000). The pump is available with power options for the UK, EU, US, AUS/CN.

Used with PIK

Designation & Ordering code

Configuration: 444.009000

444.009000

Description

Flow Control Valve

The FC1 is a pressure compensated flow control valve which can operate across a range of fluid types and is compatible with the ICM where flow rate exceeds operating parameters. Max pressure rating 400 bar at normal hydraulic system temperatures.

> Features & Benefits

- Pressure compensated
- Regulates flow to within ICM specification
- Various connection options
- Viscosity independent
- Hexagonal form for ease of installation

Dimensions



Designation & Ordering code

		ICM-FC1	
Seri	es	Configuration example: ICM-FC1	M G1
ICM	-FC1		
Flui	d compatibility		
М	Mineral oil		
Ν	Offshore fluids		
S	Phosphate ester	_	
Con	nections		
G1	ICM complete with M16x2 pressure test point connections fitted		
G3	1/4" BSP - Female port	_	
G4	7/16" UNF - Female port	_	







ICM-USBi & ICM-ETHi

Description

Auxiliary Communication Options

We offer four auxiliary communication devices to operate with the ICM 2.0:

ICM-USBi:

Two auxiliary communication devices are available to order with the ICM. A USB interface which allows for communication via a laptop (RS485 to RS232 converter) & an ethernet device for remote access via a network hub.

ICM-ETHi:

An ethernet device enables remote access via a network hub via Com Port redirection software.

Both devices can transmit power to the ICM/RDU electrical circuit using a DC power adapter.

The USBi has the additional benefit of supplying power via the USB cable directly. Both devices come with a DC Power adapter and 3m twisted pair cable as standard.

> Features & Benefits

- Compact
- Off the shelf solution
- Robust aluminium construction



Plug and play technology

- Robust aluminium construction
- Compact
- Provided with a twisted cable conductors 8, length 3m.
- All devices can transmit power to the ICM/RDU electrical circuit using the supplied DC power adapter.



ICM-USBi & ICM-ETHi



Designation & Ordering code

Configuration:	ICM	USBi
	ICM	ETHi

ICM-USBi & ICM-ETHi

() MPALTRI



SK0040

Description

Screen Filter

The SK0040 coarse screen filter adapter is designed to limit the ingress of large particles into MP Filtri's range of Contamination Monitoring Products (CMP).

> Features & Benefits

- Part number: SK0040
- Inlet connection: M16x2 male test point
- Outlet connection: M16x2 female thread form
- Pressure rating: 400 bar
- Mesh rating: 600 µm



Dimensions



Designation & Ordering code

SK0040

Configuration: SK0040

ACCESSORIES FLUID SAMPLING BOTTLES

Description

> Features & Benefits

We supply laboratory standard and certified clean sampling bottles. 100 ml, 210 ml and 500 ml bottle sizes are available and are easily incorporated into our range of bottle samplers.



Designation & Ordering code

BS110 - BS500

For Ordering Codes see page 88-91

PRESSURE & WASTE HOSES

Description

> Features & Benefits

Replacement hoses.

Pressure Hose

M16x2 Micro bore pressure hose by length (various available) long Plated steel (alternative material options available)

Pressure hoses are able to connect MP Filtri products directly to your hydraulic systems.

Waste Hose Length: 2000 mm OD: 8 mm ID: 5 mm Standard material: Polyurethane* Fitting type: Quick release coupling (brass as standard)

*Other versions available to suit the M, N and S versions of CMP



Designation & Ordering code

HOSES

For Ordering Codes see page 88-91



Filtered to perfection

Our mobile filtration units provide the perfect solution for the oil maintenance of your lubrication and hydraulic fluids in off-line filtration applications.

Benefits:

- Versatile and compact design
- Filtering and continuous cleaning of systems
- Removal of water from hydraulic systems (when fitted with a spin on filter)
- Particle counting to determine the Contamination Class according to ISO 4406, NAS 1638, AS4059

Applications:

- For oil changes, initial filling and flushing cycles in hydraulic and lubrication systems
- Pulp and paper mill equipment
- Construction machinery
- Large central hydraulic power units
- Injection moulding equipment
- Stamping presses



Mobile filtration units





UFM 015	page 103
UFM 041	113
UFM 051	119
UFM 091	125
UFM 181	131
UFM 919	137
FTU 080	143

-(101)



UFM 015

Mobile filtration unit 15 l/min flow rate







(103)

UFM 015 GENERAL INFORMATION

Description

Mobile filtration units

The UFM 015 is a portable oil transfer/filtration unit, specifically designed for both filling/transferring hydraulic oils from containers to the hydraulic tank as well as filtering and cleaning hydraulic systems.

The unit utilises Spin-On standard cartridge (supplied as option), available in two lengths, thus increasing the dirt holding capacity and lowering pressure drop of the unit.

The unit has the flexibility in being able to offer a wide range of medias and micro ratings to suit any application. The unit is very compact and lightweight.

> Features & Benefits

- Handle size
- Light
- Easy to use
- Easy maintenance
- Reliable
- Absolute filtration











Visual clogging indicator (gauge)

C E Standard

Technical data

Pump **Protection Class** IP55 Gear pump **Electric Motor** Seal NBR 0.18 kW 230 V single phase electric motor Fluid Compatibility Flow (I/min) 15 l/min - 1450 r.p.m. Mineral Oil - Other on request **Max. Operation Pressure Suction hose** lance 4.0 bar DN18 length 2500 mm DN/OD20 length 400 mm **Viscosity range Pressure hose** lance Min. operation 10 cSt DN18 length 2500 mm DN/OD18 length 400 mm Max. operation 200 cSt Max. only for cold start 400 cSt Weight 14.8 kg **Suction Filter** Type Y filtration 500 µm Equipment

Filtration Rating 3, 6, 10, 16, 25 μ m *B*>1000 flow through the element Out/In

Bypass valve ∆p set Rating 3.5 bar

Fluid Temperature From +5 °C to 60 °C

Ambient Temperature From +5 °C to 40 °C

The new concept of filtration



ELIXIR®

RFEX 160 - RETURN FILTER

Lighter, easier to use, and kinder to the environment - MP Filtri's new ELIXIR low pressure concept filters have been specially designed for in-line connections and to handle working pressures up to 1.6 MPa (16 bar).

The cast aluminium head and polyamide design reduces weight by 10% compared to the Spin-on range.

Less waste reduces both your carbon footprint and protects the environment. Replacement is fast and easy, just disassemble the bowl with a 32 mm fixed wrench , take out the FEX filter element and replace.





Designation & Ordering code

	MOBILE FILTRATION	UNIT UF	M 015							
Series	Configuration example:	UFM	015	Μ	Α	1)	0	0	P01
UFM							(
	_									
Size										
015 15 l/min	-									
Electric motor										
W 230 V single phase	-									
Soale	1									
Δ NBR										
	-									
Pressure gauges and Clogging indicators (see below)										
1 Manometer (*)						_				
Filter element										
0 Without element (for ordering, see page 26)	-									
Filtration surface					 	 				
0 Not provided	-									
Ontion										
0 No ontions	L				 	 	 			
	-									
Option	1									
P01 MP Filtri standard										

Filtration element should be ordered separately

FILTRATION SURFACE - STANDARD				
Inorganic microfibre	Wire mesh element			
FEX 160 A03 A N P01	FEX 160 M25 A N P01			
FEX 160 A06 A N P01	FEX 160 M60 A N P01			
FEX 160 A10 A N P01				
FEX 160 A16 A N P01				
FEX 160 A25 A N P01				

WATER REMOVAL	- FILTRATION SURFAC	E - STANDARD

Multi-Layer water absorber	
FEX 160 WA025 A N P01	

CLOGGING INDICATORS (*)

BVA Axial pressure gauge

Settings	Ordering code
2.5 bar ±10%	BV A 25 P01
Dimensions



(107)





Designation & Ordering code

COMF	PLETE BODY			
Series and size	Configuration example : RFEX160 E	A	B	6 P01
RFEX160				
Bypass valve				
5 Without bypass F 3 har	-			
	-			
Scale and treatments				
A NBR				
	-			
Connections	1			
B G 1 1/4"				
Connection for cloaging indicator				
6 With plugged connections				·

Execution
P01 MP Filtri standard

		FILTER	ELEMENT
Element series and size FEX160			Configuration example: FEX160 A10 A P01
Filtration ratingA03 Inorganic microfiberA06 Inorganic microfiberA10 Inorganic microfiberA16 Inorganic microfiberA25 Inorganic microfiber	3 μm 6 μm 10 μm 16 μm 25 μm	M25Wire mesh25 µmM60Wire mesh60 µmM90Wire mesh90 µmP10Resin impregnated paper10 µmP25Resin impregnated paper25 µm	
Seals and treatments A NBR			Execution

P01 MP Filtri standard



ELIXIR®

Dimensions

Mobile filtration units

(109)



RFEX SPARE PARTS

Order number for spare parts



	Q.ty: 1 pc.	Q.ty: 1 pc.
Item:	2	3 (3a ÷ 3b)
Filter series	Filter element	Seal Kit code number NBR
RFEX 160	See order table	02050772







manometer RH

Dimensions









Mobile filtration unit 34 I/min flow rate





(113

Description

Mobile filtration units

UFM 041 mobile filtration units suitable for filling and refilling of filtered hydraulic fluids and lubrication tanks.

The filter unit connected to off-line to the tank (recommended maximum volume of 350/500 L.), can be used as a support to the filtration plant on start-up for fast flushing action, either as additional filtration systems with a high incidence of contamination.

Continued use is recommended for the version with three phase electric motor.

> Features & Benefits

- Compact size
- Light
- Easy to use
- Easy maintenance
- Reliable
- Absolute filtration







GENERAL INFORMATION UFM 041

Technical data

Protection Class Pump IP55 Gear pump **Electric Motor** Seal 0.75 kW 230 V single phase electric motor NBR 0.75 kW 400/230 V three phase electric motor Fluid Compatibility Mineral Oil & Synthetic Oil - Other on request Flow (I/min) 34 l/min - 1450 r.p.m. Suction hose lance **Max. Operation Pressure** DN25 length 3000 mm DN/0D25 length 700 mm 5.0 bar **Pressure hose** lance **Viscosity range** DN20 length 3000 mm DN/OD20 length 700 mm Min. operation 10 cSt Weight Max. operation 200 cSt Max. only for cold start 800 cSt 45 kg **Suction Filter** Equipment Type Y filtration 350 µm Visual clogging indicator (gauge)

Filtration Rating 1, 3, 6, 10, 25 μm *B*>1000 flow through the element ln/Out

Bypass valve ∆p set Rating 3 bar

Fluid Temperature From -10 °C to +80 °C

Ambient Temperature From -20 °C to +45 °C **C E** Standard



Designation & Ordering code

	MOBILE FILTRATION	UNIT UFN	1 041							
Series	Configuration example:	UFM	041	Τ	A] [1	0	1	0	P01
UFM										
Size										
041 34 l/min	_									
Electric motor										
M 230 V single phase	_									
T 400/230 V three phase	_									
	-									
Seals A NDD]					
	_									
Descours reverse and Classing indicators (see below)										
Manometer (*)										
	_									
Filter element										
0 Without element (for ordering, see below)										
	_									
Filtration surface										
1 Standard										
Option										
0 No options	_									
Option										
P01 MP Filtri standard	_									
Pxx Customized	_									

Filtration element should be ordered separately

FILTRATION SURF	FILTRATION SURFACE - STANDARD			
Inorganic microfibre	Wire mesh element	Multi-Layer water absorber		
MR 250 4 A01 A P01	MR 250 4 M25 A P01	MR2504WA025AP01		
MR 250 4 A03 A P01	MR 250 4 M60 A P01			
MR 250 4 A06 A P01				
MR 250 4 A10 A P01				
MR 250 4 A16 A P01				
MR 250 4 A25 A P01				

CLOGGING INDICATORS (*)

BVA Axial pressure gauge

Settings	Ordering code
2.5 bar ±10%	BV A 25 P01

Dimensions







Mobile filtration unit 50 l/min flow rate





(119

Description

Mobile filtration units

UFM 051 mobile filtration units suitable for filling and refilling of filtered hydraulic fluids and lubrication tanks.

The filter unit connected to off-line to the tank (recommended maximum volume of 500/750 L.), can be used as a support to the filtration plant on start-up for fast flushing action, either as additional filtration systems with a high incidence of contamination.

Continued use is recommended for the version with three phase electric motor.

> Features & Benefits

- Compact size
- Continue Operation Pressure 10 bar
- Easy to use
- Easy maintenance
- ReliableAbsolute filtration
- In-line Contamination Monitor

Available in three configurations:

- configuration with start / stop differential pressure indicator visual
- configuration with start / stop automatic motor
- cut-out from differential pressure indicator electrical / visual
- configuration with start / stop phase inverter automatic motor - cut-out from differential pressure indicator - electrical / visual
- in-line Particle Counter ICM







GENERAL INFORMATION UFM

Technical data

Pump

Gear pump

Electric Motor 1.5 kW 230 V single phase electric motor 1.5 kW 400/230 V three phase electric motor with ICM 2.0

Flow (I/min) 50 l/min - 1450 r.p.m.

Max. Operation Pressure 10 bar

Viscosity range Min. operation 10 cSt Max. operation 300 cSt Max. only for cold start 800 cSt

Suction Filter Type Y filtration 800 µm

Filtration Rating 1, 3, 6, 10, 25 μ m β >1000 flow through the element Out/In

Bypass valve ∆p set Rating 3.5 bar The bypass can be blocked through the spigot

Fluid Temperature From -10 °C to +80 °C

Ambient Temperature From -20 °C to +45 °C

Protection Class IP55

Fluid Compatibility Mineral Oil & Synthetic Oil - Other on request

Suction hose lance DN32 length 3000 mm DN/0D42 length 700 mm

Pressure hose

lance DN25 length 3000 mm DN/OD30 length 700 mm

Weight 70 kg

Equipment

- Differential Clogging indicator Visual (setting 3.0 bar $\pm 10\%$)
- Differential Clogging indicator Electrical / Visual (setting 3.0 bar ±10%)
- Differential Clogging indicator Electrical / Visual with ICM 2.0 (setting 3.0 bar ±10%)

CE Standard



Designation & Ordering code

	MOBILE	FILTRATION	UNIT UFN	1 051										
Series	Configu	ration example:	UFM	051	Т	A		2	() [1	0	P01	Π
UFM	_	·												
Size														
051 50 l/min														
Electric motor M 230 V Single phase														
$\mathbf{T} = 400/230 \text{ V}$ Three phase														
Seals														
A NBR														
Pressure gauges and clogging indicators (see below)	e counter option													
2 Manometer (*) + Visual diff clogging indicator •	-	<u> </u>												
3 Manometer (*) + Electrical diff clogging indicator														
(visual indication on panel)	•													
Filter element														
0 Without element (for ordering, see below)														
Filtration surface														
1 Standard														
2 Higher							_							
FIA	ctric motor								Intic	n				
Particle counter option M	T							E P	2010 201	MP Fi	ltri sta	ndard		
0 Without ICM •	•							P	^y xx	Custo	mized	nauru		
1 With ICM 2.0 •	•							-		24010				—

Filtration element should be ordered separately

FILTRATION SURFA	WATER REMOVAL	
Inorganic microfibre	Wire mesh element	Multi-Layer water absorber
CU 400 5 A01 A N P01	CU 400 5 M25 A N P01	CU4005WA025ANP01
CU 400 5 A03 A N P01	CU 400 5 M60 A N P01	
CU 400 5 A06 A N P01		
CU 400 5 A10 A N P01		
CU 400 5 A16 A N P01		
CU 400 5 A25 A N P01		
FILTRATION SURF	WATER REMOVAL	

FILTRATION SURF	WATER REMOVAL	
Inorganic microfibre	Wire mesh element	Multi-Layer water absorber
CU 400 6 A01 A N P01	CU 400 6 M25 A N P01	CU4006WA025ANP01
CU 400 6 A03 A N P01	CU 400 6 M60 A N P01	
CU 400 6 A06 A N P01		
CU 400 6 A10 A N P01		
CU 400 6 A16 A N P01		
CU 400 6 A25 A N P01		

CLOGGING INDICATORS (*)

DVM Visual Differential Indicator		DEA Electrical Differe (visual indication	ntial Indicator on panel)
Settings	Ordering code	Settings	Ordering code
3.0 bar ±10%	DV M 30 P01	3.0 bar ±10%	DE A 30 P01



Dimensions











Mobile filtration unit 90 l/min flow rate





Description

Mobile filtration units

UFM 091 mobile filtration units suitable for filling and refilling of filtered hydraulic fluids and lubrication tanks.

The filter unit connected to off-line to the tank, can be used as a support to the filtration plant on start-up for fast flushing action, either as additional filtration systems with a high incidence of contamination. Recommended maximum tank volume of 1500/1800L.



> Features & Benefits

- Compact size
- High flow
- Continue Operation Pressure 10 bar
- Easy to use
- Easy maintenance
- Reliable
- Absolute filtration
- In-line Contamination Monitor

Available in three configurations:

- configuration with start / stop differential pressure indicator - visual

- configuration with start / stop automatic motor
- cut-out from differential pressure indicator electrical / visual
- configuration with start / stop phase inverter automatic motor - cut-out from differential pressure indicator - electrical / visual
- in-line Particle Counter ICM





GENERAL INFORMATION UFM 091

Technical data

Protection Class Pump IP55 Screw pump **Electric Motor** Seal NBR 2.2 kW 400/230V three phase 4-pole Flow (I/min) **Fluid Compatibility** Mineral Oil & Synthetic Oil - Water Glycol 90 l/min - 1450 r.p.m. **Max. Operation Pressure Suction hose** lance 10 bar DN50 length 3000 mm DN/0D50 length 700 mm **Viscosity range Pressure hose** lance Min. operation 10 cSt DN38 length 3000 mm DN/OD42 length 700 mm Max. operation 800 cSt Weight Max. only for cold start 2000 cSt 105 kg **Suction Filter** Type Y filtration 800 µm Equipment - Differential Clogging indicator - Visual (setting 3.0 bar $\pm 10\%$) **Filtration Rating** - Differential Clogging indicator - Electrical / Visual (setting 3.0 bar ±10%) 1, 3, 6, 10, 25 μ m β >1000 flow through the element Out/In - Differential Clogging indicator - Electrical / Visual - with ICM 2.0 (setting 3.0 bar ±10%) Bypass valve ∆p set CE Standard Rating 3.5 bar with bypass. The bypass can be blocked through the spigot

Fluid Temperature From -10 °C to +80 °C

Ambient Temperature From -20 °C to +45 °C



Designation & Ordering code

	MOBILE FILTRATION	UNIT UFN	N 091							
Series	Configuration example:	UFM	091	T	Α	2	0	2	0	P01
UFM										
Size										
Electric motor	_									
T 400/230 V Three phase										
Seals										
A NBR										
Pressure gauges and Clogging indicators (see below)										
2 Manometer (*) + Visual differential clogging indicate)r									
3 Manometer (*) + Electrical diff. clogging indicator										
Pillon I										
Without element (for ordering see below)						 				
Filtration surface										
2 Higher										
Option										
0 No options										
1 ICM 2.0 particle counter										
Option P01 MP Filtri standard						 			 	

Pxx Customized

Filtration element should be ordered separately

FILTRATION SU	FILTRATION SURFACE - HIGHER		
Inorganic microfibre	Wire mesh element	Multi-Layer water absorber	
CU 400 6 A01 A N P01	CU 400 6 M25 A N P01	CU4006WA025ANP01	
CU 400 6 A03 A N P01	CU 400 6 M60 A N P01		
CU 400 6 A06 A N P01			
CU 400 6 A10 A N P01			
CU 400 6 A16 A N P01			
CU 400 6 A25 A N P01			

CLOGGING INDICATORS (*)

DVM Visual Differential Indicator		DEA Ele (vi	DEA Electrical Differential Indicator (visual indication on panel)				
Settings	Ordering code	S	Settings	Ordering code			
3.0 bar ±10%	DV M 30 P01	3.0	bar ±10%	DE A 30 P01			

Dimensions



(129)





Mobile filtration unit 180 l/min flow rate





(131)

UFM 181 GENERAL INFORMATION

Description

Mobile filtration units

UFM 181 mobile filtration units suitable for filling and refilling of filtered hydraulic fluids and lubrication tanks.

The filter unit connected to off-line to the tank, can be used as a support to the filtration plant on start-up for fast flushing action, either as additional filtration systems with a high incidence of contamination. Recommended maximum tank volume of 1800/2700 L.



> Features & Benefits

- Compact size
- High flow
- Continue Operation Pressure 10 bar
- Easy to use
- Easy maintenance
- Reliable
- Absolute filtrationIn-line Contamination Monitor

Available in two configurations:

- configuration with start / stop automatic motor

- cut-out from differential pressure indicator - electrical / visual

- configuration with start / stop phase inverter automatic motor - cut-out from differential pressure indicator - electrical / visual - in-line Particle Counter ICM





Technical data

Protection Class Pump IP55 Screw pump **Electric Motor** Seal 4 kW 400/230V three phase 2-pole NBR Flow (I/min) Fluid Compatibility Mineral Oil & Synthetic Oil - Water Glycol 180 l/min - 2900 r.p.m. **Max. Operation Pressure Suction hose** lance 10 bar DN50 length 3000 mm DN/0D50 length 700 mm **Viscosity range Pressure hose** lance Min. operation 10 cSt DN38 length 3000 mm DN/0D42 length 700 mm Max. operation 800 cSt Weight Max. only for cold start 2000 cSt 109 kg **Suction Filter** Type Y filtration 800 µm Equipment - Differential Clogging indicator - Electrical / Visual (setting 3.0 bar $\pm 10\%$) **Filtration Rating** - Differential Clogging indicator - Electrical / Visual - with ICM 2.0 1, 3, 6, 10, 25 μ m β >1000 flow through the element Out/In (setting 3.0 bar ±10%) C E Standard Bypass valve ∆p set Rating 3.5 bar with bypass. The bypass can be blocked through the spigot

Fluid Temperature From -10 °C to +80 °C

Ambient Temperature From -20 °C to +45 °C



Designation & Ordering code

		MOBILE FILTRATION	UNIT UFI	M 181								
Serie	95	Configuration example:	UFM	181	T	Α	3	0	2	2	0	P01
UFM								1				
Size 181	180 l/min											
101												
Elect	tric motor											
Т	400/230 V Three phase											
Seal	S											
A	NBK											
Droo	ours gougos and Clagging indicators (ass holow)	_										
2	Manometer (*) + Electrical diff. clonging indicator											
0	(visual indication on panel)											
	· · · · ·											
Filte	r element											
0	Without element (for ordering, see below)											
Filua 2	mon surrace Higher											
<u> </u>	Tighti											
Optio	on											
0	No options											
1	ICM 2.0 particle counter											
Optio	on MD Filtri standard											
	NIP FIITI STANDARD											
F AA	00310111260											

Filtration element should be ordered separately

FILTRATION SU	RFACE - HIGHER	WATER REMOVAL
Inorganic microfibre	Wire mesh element	Multi-Layer water absorber
CU 400 6 A01 A N P01	CU 400 6 M25 A N P01	CU4006WA025ANP01
CU 400 6 A03 A N P01	CU 400 6 M60 A N P01	
CU 400 6 A06 A N P01		
CU 400 6 A10 A N P01		
CU 400 6 A16 A N P01		
CU 400 6 A25 A N P01		

CLOGGING INDICATORS (*)

Settings	Ordering code
3.0 bar ±10%	DE A 30 P01

Dimensions





(135)







Mobile filtration unit 90/180 l/min flow rate





Description

Mobile filtration units

UFM 919 mobile filtration units suitable for filling and refilling of filtered hydraulic fluids and lubrication tanks.

The filter unit connected to off-line to the tank, can be used as a support to the filtration plant on start-up for fast flushing action, either as additional filtration systems with a high incidence of contamination. Two-speed electric motor with programmable flow of 90 or 180 l/min.

> Features & Benefits

- Compact size

- High flow
- Continue Operation Pressure 10 bar
- Easy to use
- Easy maintenance
- Reliable
- Absolute filtration
- In-line Contamination Monitor

Possible applications

- Flow rate 90 l/min for filling or topping up tanks with a volume of less than 1000 liters
- Flow rate 90 l/min for depollution of tanks with a volume of less than 1000 liters
- Flow rate 90 I / min for the treatment of high viscosity oils
- Flow rate 90 I / min for a cold start phase then flow rate 180 I/min after temperature rise.

- Flow rate 180 l/min for filling or topping up tanks with a volume greater than 2000 liters
- Flow rate 180 l/min for the depollution of tanks with a volume of less than 2000 liters

Available in two configurations:

- configuration with start / stop automatic motor
- cut-out from differential pressure indicator electrical / visual
- configuration with start / stop phase inverter automatic motor
- cut-out from differential pressure indicator electrical / visual
- in-line Particle Counter ICM 2.0





GENERAL INFORMATION UP

Technical data

Pump Screw pump

Electric Motor 3.7/5 kW 400/230V three phase 2/4-pole

Flow (I/min) 90 l/min - 1450 r.p.m. / 180 l/min - 2900 r.p.m.

Max. Operation Pressure 10 bar

Viscosity range Min. operation 10 cSt Max. operation 800 cSt Max. only for cold start 2000 cSt

Suction Filter Type Y filtration 800 µm

Filtration Rating 1, 3, 6, 10, 25 μ m β >1000 flow through the element Out/In

Bypass valve ∆p set Rating 3.5 bar with bypass. The bypass can be blocked through the spigot

Fluid Temperature From -10 °C to +80 °C

Ambient Temperature From -20 °C to +45 °C

Protection Class IP55

Seal NBR

Fluid Compatibility Mineral Oil & Synthetic Oil - Water Glycol

Suction hose

lance 90° DN50 length 3000 mm DN/OD50 length 700 mm DN/OD40 length 700 mm

Pressure hose lance DN38 length 3000 mm DN/OD42 length 700 mm

lance

Weight 120 kg

Equipment

- Differential Clogging indicator Electrical / Visual (setting 3.0 bar $\pm 10\%$)
- Differential Clogging indicator Electrical / Visual with ICM 2.0 (setting 3.0 bar ±10%)





Designation & Ordering code

	MOBILE FILTRATION	UNIT UF	M 919						
Series	Configuration example:	UFM	919	Т	Α	3	0	2) P01
UFM									
Size									
919 90-180 l/min									
Electric motor									
400/230V Three phase - 2/4 pole									
0									
Pressure gauges and clogging indicators (see below)									
3 Manometer (*) + Electrical diff. clogging indicate	Ur								
Filton clomont									
Without element (for ordering see below)									
Filtration surface									
2 Higher									
Option									
0 No options									
1 ICM 2.0 particle counter									
Option									
P01 MP Filtri standard									

Pxx Customized

Filtration element should be ordered separately

FILTRATION SUR	WATER REMOVAL	
Inorganic microfibre	Wire mesh element	Multi-Layer water absorber
CU 400 6 A01 A N P01	CU 400 6 M25 A N P01	CU4006WA025ANP01
CU 400 6 A03 A N P01	CU 400 6 M60 A N P01	
CU 400 6 A06 A N P01		
CU 400 6 A10 A N P01		
CU 400 6 A16 A N P01		
CU 400 6 A25 A N P01		

CLOGGING INDICATORS (*)

|--|

3.0 bar +10% DE A 30 P01	Settings	Ordering code
	3.0 bar ±10%	DE A 30 P01

Dimensions

Mobile filtration units

(141)



() MPALTRI




Fluid transfer unit with ICM 2.0 (In-line Contamination Monitor)





143

Description

Fluid Transfer Unit

FTU 080 Fluid Transfer unit suitable for filling, recirculation - via onboard 80L reservoir - and emptying of filtered hydraulic fluids and lubrication tanks.

The FTU can be utilised either as additional filtration to a system with a high incidence of contamination, or can be used as a standalone recirculating filtration circuit to clean fluid to a predetermined contamination level - monitored by the onboard ICM - prior to transfer of fluid to the system.

> Features & Benefits

- Compact size
- Easy to use
- Easy maintenance
- Reliable
- Absolute filtration
- In-line Contamination Monitor

Possible applications

- Low flow rate for filling of reservoirs
- Low-flow filtration for off-line tanks
- Pre filtration ability of fluid prior to filling of hydraulic system







Technical data

Pump Gear pump

Electric Motor 0.75 kW 1400 rpm, 110/230 V single phase

Flow (I/min) 15 I/min

Max. Operation Pressure 3.5 bar

Inlet (pump protection) filtration steel 250 µm strainer

Viscosity 150 cSt maximum fluid viscosity

Suction Filter 250 µm metal mesh strainers

Bypass valve ∆p set Rating 3.5 bar with bypass

Filtration Water removal "spin-on" type, bypass set at 1.75 bar. In-line filtration 3 μ m absolute *B* 1000 element bypass set at 3.0 bar.

Filtration rating See designation order for cartridge and filter elements

Control Electrical Control Box Indicator Delivery line electric cut out switch

Ambient Temperature From -10 °C to 80 °C

Working temperature From 0 °C to 40 °C

Protection Class

Seal NBR

Fluid Compatibility Mineral oil compatible - please contact sales team for queries about other fluids

Hoses Flexible hoses - SAE100R4 1" BSP swaged females 2mtr long hose

Oil level Sight glass and filler with integrated electric float cut out switch

Weight 200 kg

Mounting Heavy duty trolley and wheels

CE Standard



Designation & Ordering code

		FLUID TRAN	SFER UNIT	FTU								
Mobile	filtration unit	Configuratio	n example:	FTU	1	1	15	2	2	1 M	250	SL4305
FTU	Fluid Transfer Unit	=										
Onhoo												
1	80 litres											
<u> </u>		-										
In-line	contamination monitor											
1	With ICM	_										
Elow r	ato											
15	15 l/min											
		_										
Motor	power											
2	0.75 kW, 1400 rpm	_										
Vage												
1	110 V - 50 Hz single phase									_		
2	240 V - 50 Hz single phase	_										
In lot fi												
	CFO una susting strainer (internel of recompoin)											
WI250	250 µm suction strainer (Internal of reservoir)		-									
Outlet	filtration					 						
SL430	5 Single spin on plus LMP length 5					 						

Filtration element is not included and should be ordered separately.

Outlet filtration options:

LMP: CU400 5 A03, A06, A10, A16, A25 - SPIN-ON: CS150 A03, A06, A10, A25 - CS150 P10, P25 - WATER REMOVAL: CW150 P10, P25

CARTRIDGE STANDARD LENGTH					
Inorganic microfibre	Wire mesh element				
CS 100 A01 A P01	CS 100 M25 A P01				
CS 100 A03 A P01	CS 100 M60 A P01				
CS 100 A06 A P01					
CS 100 A10 A P01					
CS 100 A25 A P01					

CARTRIDGE EXTENDED LENGTH						
Inorganic microfibre	Wire mesh element					
CS 150 A01 A P01	CS 150 M25 A P01					
CS 150 A03 A P01	CS 150 M60 A P01					
CS 150 A06 A P01						
CS 150 A10 A P01						
CS 150 A25 A P01						

LMP FILTER ELEMENT - LENGTH	5
-----------------------------	---

Inorganic microfibre
CU 400 5 A03 A N P01
CU 400 5 A10 A N P01
CU 400 5 A16 A N P01
CU 400 5 A25 A N P01

WATER REMOVAL - CARTRIDGE EXTENDED LENGTH

Multi-Layer water absorber CW150P10A

FTU 080

Dimensions









	Makila fillasi'a





-(151)

All data, details and words contained in this publication are provided for use by technically qualified personnel at their discretion, without warranty of any kind.
 MP Filtri reserves the right to make modifications to the models and versions of the described products at any time for both technical and/or commercial reasons.
 For updated information please visit our website: *www.mpfiltri.com* The colors and the pictures of the products are purely indicative.
 Any reproduction, partial or total, of this document is strictly forbidden.
 All rights are strictly reserved



(152)





WORLDWIDE NETWORK



CANADA CHINA FRANCE GERMANY INDIA RUSSIAN FEDERATION SINGAPORE UNITED ARAB EMIRATES UNITED KINGDOM USA

PASSION TO PERFORM

