



LPA3

LPA3

Portable Particle Counter

TAKE THE LAB WITH YOU WHEREVER YOU GO

AVIATION FLUIDS



PASSION TO PERFORM

Designed, engineered & manufactured by MP Filtri UK

LPA3

The world's most advanced and versatile mainstream portable particle counter

Whether you are working in the lab or in the field, MP Filtri's next-gen LPA3 delivers a fast, accurate and comprehensive hydraulic health check in a robust yet portable package.

The LPA3 delivers particle counting to all international standards, as well as moisture and temperature measurement. Its real-time monitoring and proactive maintenance safeguards machinery, enhances performance and productivity, and reduces costs and unplanned downtime

Featuring the latest breakthroughs in optical and photodiode technology, the new LPA3 enhances the reliability and longevity of complex hydraulic systems and is ideal for systems quality control in in-house manufacturing applications.



LPA3 SETS NEW STANDARDS



ACCURACY

Using the latest LED optical technology, the LPA3 is accurate to \pm 1/2 code for 4, 6, 14 μ m(c).



MOBILITY

Highly durable and yet perfectly portable - weighing in at just 10 kg (22 lb).



ANALYSIS

Real-time monitoring and proactive maintenance.



SPEED

High-speed sample times over 16 times quicker than the LPA2.



EFFICIENCY

Slashes costs and downtime, protects machinery and rapidly pays for itself.



EASE OF USE

Sophisticated yet simple to use, the LPA3 can be mastered without formal training.



Instant results

download

via USB




All the benefits of the laboratory in the field

The LPA3 is robust and light - weighing in at just 10 kg, and its ergonomic space-efficient design enables operators to work effectively in a wide variety of challenging work environments - without having to make sacrifices to functionality.



Market-leading versatility

Not only is the LPA3 designed to thrive in a wide range of sectors and applications, the machine can also be personalised for peak performance with operators able to tailor sample volumes and flush sizes; the amount of tests run concurrently; Capable of completing the 100ml sample test in just one minute.



Range of different connections

Easy-fit standard hydraulic connections maintain high environmental protection ratings. USB data connection enables rapid download of results to a data stick.

A: M16 x 2 Test point connection

B: Quick-release waste capture

C: USB data stick download port

D: PC-USB connection

E: Power on/off with built in bi-colour LED

F: IP rated DC charging port



Wide range of reporting formats

Wherever you are working and whatever standards you are using we've got you covered. We've also added five* new reporting standards.



Easy to use interface

Simple yet sophisticated software; highly responsive touchscreen with no need for a stylus; and a customisable home screen for all your key performance information at-a-glance.



Fast, smooth learning curve

Designed for ease of
use, the LPA3 enables first time
operators to get up and running
in minutes - without the need for a
dedicated training programme. The
machine's sophisticated functionality
sets new standards in the industry
but is surprising easy to master, saving
customers time and money.



LPA3 Specification



Technology	High precision LED light extinction automatic optical particle counter
Particle Sizing	>4, >6, >14, >21, >25, >38, >50, >70 μm(c)
Analysis Range	ISO 4406 Codes 8 to 24 NAS 1638 Class 2 to 12 AS4059/ISO 11218 Rev E, Table 1 Size Codes 2-12 AS4059/ISO 11218 Rev E, Table 2 Size Codes, A:000 TO 12, B:00 to 12, C: 00 to 12, D: 2 to 12, E: 4-12, F: 7 to 12 AS4059 Rev F, Table 1 Size Codes 2-12 AS4059 Rev F, Table 2 Size Codes cpc [000 to 12, 00 to 12, 00 to 12, 2 to 12, 4 to 12, 7 to 12] GBT14039 Codes 8-24 GJB420B Size Codes, A:000 to 12, B:00 to 12, C: 00 to 12, D: 2 to 12, E: 4-12, F: 7 to 12 Please Note: (Lower Limits are Test Volume dependent)
Accuracy	\pm 1/2 ISO code for 4, 6, 14 μ m(c) \pm 1 code for 21, 25, 38, 50, 70 μ m(c)
Calibration	Individually calibrated with ISO Medium Test Dust (MTD) based on ISO 11171, on equipment certified by I.F.T.S. ISO 11943
Viscosity Range	Up to 400 cSt
Fluid Temperature	Minimum: -25°C / +41°F Maximum: +80°C / +176°F
Ambient Temperature	Minimum: -10°C / +14°F Maximum: +80°C / +176°F
Pressure	Minimum: 2 bar / 29 PSI Maximum: 420 bar / 6091 PSI
Sample Volume / Test time	Maximum 100 ml per pump stroke. Test volumes programmable by end user
Moisture Sensing	% RH (Relative Humidity) ±3%
Temperature Measurement	±3%
Data Storage	Approximately 4000 timestamped tests in the integral LPA3 memory
Environmental Protection	IP 66 (Lid closed) IP54 (Lid open)
Power	Long-life Lithium Ion internal rechargeable battery (mains charger)
Weight / Dimension	10 kg, Height 292 mm, Depth 155 mm, Width 435 mm





Mobile

Portable and precise, the LPA3 is ideal for applications where accuracy is vital even in challenging and variable working conditions.



Offshore

Capable of handling aerospace phosphate ester, mineral and synthetic oil, subsea/ offshore

water based fluids and more....



Industrial

Keeps production lines working at full capacity – ensuring the best in performance and productivity.



Aviation

Minimises aircraft on ground downtime, dramatically reducing operational and maintenance costs.



Test rigs

Delivers accurate and reliable comprehensive hydraulic health checks to a host of international standards.



Machine tools

Ideal for precision tooling, injection moulding, presses and power packs - supports a wide range of industries.



Why choose MP Filtri as your partner for contamination control solutions?

MP Filtri prides itself on being the original and the best when it comes to portable particle counters.

The celebrated LPA2 set new standards in the industry at launch - and this new incarnation enhances and improves the original machine's market-leading functionality - delivering faster results, greater accuracy, more storage, extensive customisation options, and a more robust and portable design.

MP Filtri has a proud heritage spanning more than 50 years as an innovator in the hydraulic filtration industry and has forged a growing reputation for the quality of its products and its customer service.

When the vast majority of hydraulic failures are caused by contamination - can you afford not to team up with MP Filtri and ensure your machinery is maximising its efficiency and potential?

Our Product Ranges

Portable Particle Counters

Innovative products to suit a variety of sectors and budgets from the CML 2.0 to the Airbus approved Aviation edition LPA2.



Bottle Samplers

A choice of 110ml and 500ml models, ideal for use in laboratories where fluid sampling at point of use is inaccessible or impractical.



0 0 0 0 0 0 1 CM 2.0


In-line Contamination Monitors

Our market-leading ICM 2.0 and ICU models deliver the ultimate hydraulic health checks and are also Industry 4.0 ready.



Off-line Filtration Units

A comprehensive range of offline filling and filtration units to help service and maintenance teams deliver outstanding oil and hydraulic fluid cleanliness.



(*) N and S version, moisture sensor (W) not available Available with Screen Protector (Part number 63.095000). Consult your local branch for further details

HEADQUARTERS

MP Filtri S.p.A.

Pessano con Bornago, Milano - Italy sales@mpfiltri.com

BRANCH OFFICES

ITALFILTRI LLC

Moscow - Russia mpfiltrirussia@yahoo.com

MP Filtri Canada Inc.

Concord, Ontario - Canada sales@mpfiltricanada.com

MP Filtri France SAS

Lyon, AURA - France sales@mpfiltrifrance.com

MP Filtri Germany GmbH

St. Ingbert - Germany sales@mpfiltri.de

MP Filtri India Pvt. Ltd.

Bangalore - India sales@mpfiltri.co.in

MP Filtri (Shanghai) Co., Ltd.

Shanghai - P.R. China sales@mpfiltrishanghai.com

MP Filtri U.K. Ltd.

Bourton on the Water, Gloucestershire - United Kingdom sales@mpfiltri.co.uk

MP Filtri U.S.A. Inc.

Quakertown, PA - U.S.A. sales@mpfiltriusa.com



MP Filtri SEA PTE Ltd.

Singapore sales-sea@mpfiltri.com



All information stated in this brochure is correct at time of printing and subject to change without notice.