



# PASSION TO PERFORM





# MPFX, MPTX, MRSX The New Filter Concept

The Massachusetts Institute of Technology - M.I.T. Boston (US) have established, according to the study made by Dr. E. Rabiniwicz, that the presence of solid particles in the hydraulic fluid is the most important factor influencing the reliability and life of fluid systems.



#### THE TRUE VALUE OF THE MACHINE IS THE RIGHT FUNCTIONALITY OF ITS HYDRAULIC SYSTEM

DO YOU KNOW HOW MANY FILTER ELEMENTS ARE SUPPLIED WITH EACH MACHINE YOU SELL EVERY YEAR?

> DO YOU KNOW HOW MANY FILTERS ELEMENTS ARE REPLACED IN YOUR MACHINES EVERY YEAR?

DO YOU KNOW THE DURATION OF LIFE OF YOUR MACHINE?

#### TO ENSURE MACHINE RELIABILITY, QUALITY AND EFFICIENCY, THE FILTER ELEMENT IS THE COMPONENT TO BE REPLACED!



PROTECT LIFE AND PERFORMANCE OF YOUR MACHINE BY ONLY USING ORIGINAL SPARE PARTS!



# THE CONCEPT MPFX MPTX MRSX

Tank Top Mounted Return and Return/Suction filters series specifically designed for all mobile hydraulic systems in utility vehicles, agricultural and contruction machinery





Filter element featuring our UNIQUE end cap with polygonal design.



UNIQUE polygonal spigot fitting within the filter bowl.

The products identified as MPFX, MPTX, MRSX, MFBX, MFX and RSX are protected by one or more of the following patents:



Italian Patent: n° 102014902261205 European Patent Pending: n° 16181725.9

US Patent Pending: n° 15/224,337

Canadian Patent Pending: n° 2,937,258

Protects the machine from improper use of non-original products

> Increases the reliability of the machine

Helps OEMs to increase RELIABILITY and PROFIT

#### MPFX Return Filter

- Max. working pressure 8 bar (116 psi)
- Flow rates up to 900 I/min (238 gpm), oil flow external to internal
- Microfiber filter element, with absolute filtration rating in compliance with new MULTIPASS TEST ISO 16889
- Paper filter element, with nominal filtration rating using mineral oil according to ISO 2943
- Electrical/optical contamination indicator available as accessory
- Other options/accessories: extension pipe, diffuser for the oil outlet, multiple inlet connections for several sizes

All technical specifications and additional features relating to the MPFX are completely interchangeable with the MPF series.



- Max. working pressure 8 bar (116 psi)
- Flow rates up to 300 l/min (79 gpm), oil flow external to internal
- Microfiber filter element, with absolute filtration rating in compliance with new MULTIPASS TEST ISO 16889
- Paper filter element, with nominal filtration rating using mineral oil according to ISO 2943
- Simple element replacement
- Electrical/optical contamination indicator available as accessory
- Other options/accessories: oil dipstick, extension pipe, diffuser for the oil outlet, multiple inlet connections for several sizes

All technical specifications and additional features relating to the MPTX are completely interchangeable with the MPT series.



Standard Length			
1	2	3	4
•			
٠	•	•	•
٠	٠		
	٠		
٠	٠	٠	
٠			
			-



	Standard Length			
Size	1	2	3	4
025-027	•	٠	٠	
110-114-116 120	•	•	•	•

### MRSX Return/Suction Filter

- Max. working pressure 10 bar (145 psi)
- Flow rates up to 250 l/min (66 gpm), oil flow external to internal
- Microfiber filter element, with absolute filtration rating in compliance with new MULTIPASS TEST - ISO 16889
- Specifically designed for closed loop systems within Hydrostatic Drives



Size	Standard Length			
	1	2	3	4
116	•	•		
165-166	٠	٠	٠	





### WORLDWIDE NETWORK



# PASSION TO PERFORM

CMP3AUS004R Rev. 04/2021

## www.mpfiltri.com